

# PTFE Shielded and Jacketed Cables

600 Volts — 200°C Silver Plated Copper

600 Volts — 260°C Nickel Plated Copper



High temperature shielded cables



Planetary Twister

AWG SIZE	STRANDS	NOMINAL DIAM. OVER		1 CONDUCTOR		CATALOG NUMBER
		COND.	INSUL.	NOMINAL DIAM. OVER*		
				SHIELD	CABLE	
32	7 x .0031	.009	.029	.047	.070	E327-1CSTJ E327-1CSFJ E327-1CSGB
30	7 x .0040	.012	.032	.050	.073	E307-1CSTJ E307-1CSFJ E307-1CSGB
28	7 x .0050	.015	.033	.055	.078	E287-1CSTJ E287-1CSFJ E287-1CSGB
26	7 x .0063	.019	.038	.060	.083	E267-1CSTJ E267-1CSFJ E267-1CSGB
26	19 x .0040	.019	.038	.060	.083	E2619-1CSTJ E2619-1CSFJ E2619-1CSGB
24	7 x .0080	.024	.043	.065	.088	E247-1CSTJ E247-1CSFJ E247-1CSGB
24	19 x .0050	.025	.043	.065	.088	E2419-1CSTJ E2419-1CSFJ E2419-1CSGB
22	7 x .0100	.030	.049	.071	.094	E227-1CSTJ E227-1CSFJ E227-1CSGB
22	19 x .0063	.030	.049	.071	.094	E2219-1CSTJ E2219-1CSFJ E2219-1CSGB
20	7 x .0126	.038	.058	.080	.103	E207-1CSTJ E207-1CSFJ E207-1CSGB
20	19 x .0080	.038	.058	.080	.103	E2019-1CSTJ E2019-1CSFJ E2019-1CSGB
18	19 x .0100	.047	.068	.090	.113	E1819-1CSTJ E1819-1CSFJ E1819-1CSGB
16	19 x .0113	.053	.075	.097	.120	E1619-1CSTJ E1619-1CSFJ E1619-1CSGB
14	19 x .0142	.067	.090	.112	.135	E1419-1CSTJ E1419-1CSFJ E1419-1CSGB
12	19 x .0179	.084	.111	.133	.156	E1219-1CSTJ E1219-1CSFJ E1219-1CSGB