

RoHS Compliant: YES

BODINE INSTRUCTIONS REQUIRED (UNLESS OTHERWISE SPECIFIED):
 PURDI-551-01 FOR CORD MOTORS AND GEARMOTORS



NOTES:

1. CORD MUST CONFORM TO UL 758 & CSA C22.2 NO. 210
2. THE FOLLOWING MINIMUM INFORMATION IS TO BE LEGIBLY PRINTED [OR INDENTED] AT INTERVALS OF 24" OR LESS.
 - MFR'S IDENTIFYING MARK OR U.L. FILE No.
 - CORD TYPE LETTER DESIGNATION.
 - NUMBER & SIZE OF CONDUCTORS.
 - TEMPERATURE RATING
 - VOLTAGE RATING
3. SHIELD: ALUMINUM/MYLAR-ALUMINUM FACING INWARD
4. MUST BE UL AWM STYLE 2661.

REFERENCE ONLY:

MANUFACTURER

MANUFACTURER'S P/N

PART NO./REV. 49001075 A	
CORD BULK PVC 24/4 105C 2661 SHLDDR	
CORD BULK 4 CONDUCTOR DRAIN/SHIELD	
GRAPHIC NO: 490AA058.A	DESIGNER: MZM
eDOC NO: 20150049	SCALE: NONE
	PHASE-IN DATE: 6/30/2014
	PHASE-OUT DATE: 12/31/2079
UNLESS OTHERWISE SPECIFIED: UNITS ARE IN INCHES [mm]	
TOLERANCES: .XX:±.01 .XXX:±.005 ANGLES: X'±3' X.X':±0.5'	
BODINE ELECTRIC COMPANY	

