

Description: Four 24 AWG Conductors
 With An Overall Foil Shield
 and PVC Jacket

Date: 6/4/2014

JM Part Number: TBD

Reference: 2404COFS-8JM

Components Four 24 AWG Insulated Conductors

Conductor: 24 AWG, 7/32 tinned copper

Insulation: .009" nominal wall of SR-PVC (see below for color code) .042"

Cable Construction

Cabling: Four Conductors

Drain Wire: 24 AWG, 7/32 tinned copper

Shield: Aluminum-Mylar tape, Aluminum side IN, 100% coverage

Jacket: .020" nominal wall of Gray PVC .145"

Print

E138031 4/C 24 AWG SHIELDED 105C (UL) TYPE CM - - - LL41103 CSA CMG 60C FT4

Color Code

1. Black 2. White 3. Red 4. Green

Requirements

Temperature: 105C

Voltage: 600V (Non-UL)

Approvals: UL Type CM

CSA CMG

Materials are RoHS Compliant
 (2011/65/EU)

Written By:	rjc	6/4/2014	Rev. 0	Initial Issue
Revised By:	rjc	6/9/2014	Rev. 1	Added customer part number
Revised By:	rjc	6/26/2014	Rev. 2	Changed drain wire to 7 strand, added coverage to shield and voltage requirements
Revised By:	scs	9/24/2014	Rev. 3	Change CSA approvals