



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: info@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

6-Mar-2014

Product Number : **5152452TFT4.1**

RoHS

**O/A SH CABLE 2/PR 24/7 AWG Tinned Copper
SR-PVC Insulation
PVC FT4 Jacket**

Conductor : 24 AWG 7 Strand Tinned Copper Cond.	
Total Cable Weight : 34 kg/km	Final Diameter : 0.206 inches
Insulation : SR-PVC	Jacket : PVC
Shield : Foil Shield	
Drain : 24 AWG 7 Strand Tinned Copper	
DC Resistance 25°C: 15.6 Ohms / 1000 ft	Mutual Capacitance : 24.2 pF/ft
Impedance : 80 Ohms	Cond to Shield Cap. : 42.3 pF/ft
Velocity of Prop : 63 %	Inductance. : 1.3 mH/km

Print Notes :

Standard Print : ECI CSA CMG 105°C OR AWM II A/B 105°C LL61365 600V FT-4 RU AWM
E107863 STYLE 2464 300V VW-1 20 AWG RoHS

(All of the above values are approximated to within +/- 10%)