



For more Information  
please call

1-800-Belden1



### General Description:

24 AWG stranded (7x32) TC conductor, plenum, foam FEP insulation, twisted pairs, individually shielded w/Beldfoil (100% coverage), 24 AWG stranded TC drain wire, Flamarrest® jacket.

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (mm)
2	24	7x32	TC - Tinned Copper	0.6096

Total Number of Conductors: 4

#### Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
FFEP - Foam Fluorinated Ethylene Propylene	0.483

#### Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG
24

Inner Shield Drain Wire Stranding: 7x32

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material	Nom. Wall Thickness (mm)
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.356

#### Overall Cable

Overall Nominal Diameter: 6.477 mm

#### Pair

Pair Color Code Chart:

Number	Color
1	White/Blue & Blue/White
2	White/Orange & Orange/White

### Mechanical Characteristics (Overall)

Operating Temperature Range: 0°C To +75°C

Bulk Cable Weight: 35.717 Kg/Km

Max. Recommended Pulling Tension: 146.791 N

Min. Bend Radius/Minor Axis: 69.850 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

## METRIC MEASUREMENT VERSION

## 82729 Multi-Conductor - Multi-Pair Snake Cable

EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes

### Flame Test

UL Flame Test:	NFPA 262
CSA Flame Test:	FT6

### Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	9729

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)	100
-----------------	-----

### Nom. Inductance:

Inductance ( $\mu\text{H/m}$ )	0.78744
--------------------------------	---------

### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)	44.2935
--------------------	---------

### Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)	73.8225
--------------------	---------

### Nominal Velocity of Propagation:

VP (%)	76
--------	----

### Nominal Delay:

Delay (ns/m)	4.2653
--------------	--------

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)	78.744
---------------------	--------

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 47.246 Ohm/km

### Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
.384	2.42794
.7056	2.85447
.768	2.92009
1.024	3.11695
1.4112	3.37943
1.536	3.47786
2.048	3.83877
2.8224	4.49497
3.072	4.72464
4.096	5.47927
5.6448	6.20109
6.144	6.43076
8.192	7.41506
11.2896	8.49779
12.288	8.89151
24.576	12.2381

### Max. Operating Voltage - UL:

Voltage	300 V RMS
---------	-----------

### Max. Recommended Current:

Current	2.0 Amps per conductor @ 25°C
---------	-------------------------------

### Notes (Overall)

**Notes:** Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
82729 877U1000	1,000 FT	26.000 LB	NATURAL		2 PR #24 FFEPR FS FLMRST
82729 8771000	1,000 FT	28.000 LB	NATURAL	C	2 PR #24 FFEPR FS FLMRST

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 09-25-2012

© 2015 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.