

**Description:** Five 24 AWG Insulated Conductors  
 Overall PU Jacket

**Date:** 9/22/2017

**JM Part Number:** JM57932

**Reference:** 2405COFS-9DGA

**Components** Five 24 AWG Insulated Conductors

Conductor: 24 AWG, 41/40 tinned copper

Insulation: .010" nominal wall of SR-PVC (see color code) .044"

**Cable Construction**

Cabling: Five conductors cabled with FR PP Fillers

Drain Wire: 24 AWG, 7/32 tinned copper

Shield: Aluminum-Mylar tape, Aluminum side IN

Ripcord: Nylon

Jacket: .032" nominal wall of White PU .187"

**Print (Black Inkjet)**

**E66440 5/C 24 AWG SHIELDED 9\ AWM 20233 80C 300V VW-1 ---**  
**LL41103 CSA AWM I/II A/B 80C 300V FT1**

**Color Code**

1. Black 2. Red 3. White 4. Green 5. Orange

**Requirements**

Temperature: 80°C  
 Voltage: 300V

Approvals: UL AWM Style 20233, VW-1  
 CSA AWM, FT1  
 Materials are RoHS Compliant  
 (2011/65/EU & EU 2016/863)

Written By:	scs	9/22/2017	Rev. 0	Initial Issue
Revised By:	scs	10/23/2017	Rev. 1	
Revised By:				
Revised By:				