

Aerospace Part#: TBD

CONTROL CABLE

DESCRIPTION

6 Conductors AWG 24/19x36 SPC
Overall Braid Shielded PTFE/PTFE White 600V 200C

PHYSICAL PROPERTIES

Conductors

Insulation

# Conductors	AWG	Material	Material	Wall	Finished OD
6	24/19x36	Silver Plated Copper	PTFE	.010"	.043"

Outer Braid Material

Layer 1 Type	Material	AWG	Coverage
Overall Braid	Silver Plated Copper	38	90%

Outer Jacket Material

Cabling

Jacket Material	Color	Wall	Overall O.D.	Lay
PTFE	White	.012"	.182" Nom.	6" Lay on Cable

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
Rated -65C to 200C	35.8 lbs / m	10 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage
Rated 600 Volts

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

Reach / RoHS Compliant	YES
Suitability	Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasian, Acid
Flame Test	NFPA 262 / FT6

MISCELLANEOUS

Color Code: Black / Red / White / Green / Yellow / Blue /

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

* Specification subject to error and may change without notice