



## SPECIFICATION OUTLINE

Date: May 30, 2013

Customer: Industrial Electric Wire & Cable

Industrial Electric Wire & Cable P/N: TBD

EIS Wire & Cable P/N: 80624014014

Description: Six conductor shielded cable manufactured as C(UL)US type CMG per NEC Article 800 or UL AWM Style 2464.

Conductors: (6) 24 AWG stranded (7/32) tinned copper conductors.

Insulation: 9 mils minimum average of 80°C rated Semi Rigid PVC.

Nominal O.D. over insulation: .043”

Fillers: Fibrillated foamed polypropylene fillers used for roundness.

Shield: Aluminum / polyester tape helically applied with the foil side facing out.

Drain wire: (1) 24 AWG stranded (7/32) tinned copper drain wire, applied over and in contact with the aluminum polyester tape

Jacket: 32 mils of 80°C rated PVC.

Nominal O.D.: .197”

Jacket color: Chrome Gray

Surface print: “E113422 24 AWG 75C C(UL)US CMG FT4 OR AWM STYLE 2464 80C 300 VOLTS ”

Color Rotation: Black, White, Red, Green, Brown, Blue

RoHS Compliant: YES

Put-ups: 1,000 ft. +/- 10% on non-returnable wood reels.

053013DL