

1) CONSTRUCTION:		NOM. DIA.
CONDUCTOR:	24 AWG 7/32 STRANDED TINNED COPPER	.024"
INSULATION:	POLYVINYLCHLORIDE, .010" NOM. WALL THICKNESS	.044"
CABLE:	(6) INSULATED CONDUCTORS TWISTED TOGETHER TO FORM A CABLE CORE	.130"
SHIELD:	ALUMINIZED POLYESTER FOIL SHIELD (FOIL OUT, 100% COVERAGE) WITH A 24 AWG STRANDED TINNED COPPER DRAIN WIRE CONTACTING THE METALIZED SURFACE FOR EASY TERMINATION.	.134"
JACKET:	POLYVINYLCHLORIDE, CHROME GRAY, .032" NOM. WALL THICKNESS	OVERALL CABLE DIAMETER .200"

2) PHYSICAL PROPERTIES:	
TEMPERATURE RATING, MAX.	60°C & 80°C
TEMPERATURE RATING, MIN.	-20°C
WT./M', NOM., NET.	23.9 LBS.

3) ELECTRICAL CHARACTERISTICS:	
CAPACITANCE, MUTUAL, NOM.	33 PF/FT.
CAPACITANCE, GROUNDED, NOM.	65 PF/FT.
DIELECTRIC WITHSTANDING, MIN.	2000V RMS
VOLTAGE RATING, MAX.	300V
D.C. RESISTANCE, MAX. PER ASTM B286	26.2 Ω/M'


4) AGENCY APPROVALS:
 NEC (UL) TYPE CM
 (UL) AWM STYLE 2464
 CSA AWM FT4

5) APPLICATION:
 RS-232 COMPUTER INTERCONNECT, INSTRUMENTATION, SOUND, BROADCAST, CLASS 2 CIRCUITS.
 RoHS COMPLIANT MATERIALS.

6) PRINT:
 QUABBIN 8180 (UL) TYPE CM 24 AWG SHIELDED OR AWM 2464 -- CSA LL51726 AWM I/II A/B 80C 300V FT4 -- RoHS -- **(LOT DESIGNATOR)**

- 7) COLOR CODE:
1. BLACK
 2. WHITE
 3. RED
 4. GREEN
 5. BROWN
 6. BLUE

8) PACKAGING
 TO BE PACKAGED AS PER QWC'S
 STANDARD PACKAGING



Created 09/21/95	BMD DRAWN: 09/10/15	
REV. 07	CHECKED: GBM 09/11/15	
TITLE 6/C 24 AWG PVC/PVC SHIELDED CABLE -- TYPE CM, STYLE 2464, CSA AWM FT4		
QUABBIN P/N	8180	1 of 1

CUSTOMER APPROVAL:

DATE: