

Deca Cables Inc.

150 North Murray Street
PO Box 777
Trenton, ON
Canada
K8V 5W6

Telephone: (613) 392-3585

Fax: (613) 392-7908

ISO 9002 - 1994

PRODUCT DATA SHEET

PART NUMBER	76-453
DESCRIPTION	AWM FOAM/PVC 3PR 24/7T LC 65%T CSA FT4
CONDUCTOR	24 AWG TINNED COPPER
STRANDING	7 X 0.0080"
CONDUCTOR DIAMETER	0.024"
INSULATION	POLYETHYLENE FOAM
INSULATION THICKNESS	0.010"
INSULATED COND. DIAMETER	0.045"
RESISTANCE	25.7 OHMS/1000FT.
BRAID	36 AWG SOLID 0.0050 TINNED 65%
CAPACITANCE	12.5 PF/FT
SHIELD	ALUM / MYLAR TAPE
DRAIN	24 AWG 7 X 0.0080 TINNED
RIPCORD	POLYESTER RIPCORD UNDER JACKET
JACKET	PVC (80C)
JACKET THICKNESS	0.030"
FINISHED DIAMETER	0.258"
FLAME RATING	FT4
CSA CERTIFIED	CMG
UL RECOGNIZED	AWM STYLE 2919

The material contained in this document is presented in good faith and believed to be reliable and accurate. However, because testing conditions may vary and material quality or information that may be provided in whole or part by others may be beyond our control, no warranty, expressed or implied, is given and Deca Cables Inc. can assume no liability for results obtained or damages incurred through the application of the data and tests presented.

Rev.0
2002.08.06