

**Contact**

Copper LAN Product Inquiry  
Phone: 717-354-6200  
berktek.support@nexans.com

**LANmark-350 Patch**

**LANmark-350 Patch**

**Part Number: 10032641**

Berk-Tek's LANmark-350 Premium Category 5e UTP cables are designed to meet the most advanced UTP horizontal cable applications. Tested up to 350 MHz, the guaranteed performance of this cable far exceeds the ANSI/TIA/EIA-568-C.2 and ISO/IEC 11801 horizontal cable requirements for PS-NEXT, attenuation, structural return loss, attenuation-to-crosstalk ratio (ACR) and impedance, making it ideal for high-end transmission links supporting today's networking protocols.

**Description**

**Construction**

Stranded tinned copper wire insulated with polyethylene. Two insulated conductors twisted together to form a pair and four such pairs cabled to form the basic unit jacketed with flame-retardant PVC.

**Standards**

- North American: ANSI/TIA/EIA-568-C.2, UL 444 and C22.2 No.214-02
- International: ISO/IEC 11801-2nd Edition Category 5, EU Directive 2002/95/EC (RoHS)

**Flame Rating**

- Patch - UL 1685, CM, IEC 332-1
- UL Listed

**Features**

- Small, round design
- ETL verified to TIA/EIA-568-C.2 and ISO/IEC 11801

**Benefits**

- Reliably supports 100BASE-TX Ethernet
- Reduced installation costs and maintenance
- Characterized to 450 MHz, 350 MHz greater than standard
- Lower bit error rates, increases network efficiency and uptime

**Standards**

**International** ISO/IEC 11801

**National** ANSI/TIA-568-C.2; UL 444

## LANmark-350 Patch

LANmark-350 Patch  
Part Number: 10032641

### Characteristics

Construction characteristics	
Type of cable	UTP
Colour	Black
Dimensional characteristics	
Length per reel	1000.0 ft
Number of pairs	4
Usage characteristics	
Packaging	Reel
Field of application	Indoor
Category	Cat. 5e
Fire safety	CM

### Technical Data - Physical

Technical Data - Physical			Color Code		
<b>Conductor</b>	24 AWG Stranded TC		<b>Pair-1</b>	White/Blue	Blue
<b>Conductor diameter—in. (mm)</b>	0.024	(0.61)	<b>Pair-2</b>	White/Orange	Orange
<b>Insulated Conductor Diameter- in. (mm)</b>	0.04	(1.02)	<b>Pair-3</b>	White/Green	Green
<b>Cable diameter—in. (mm)</b>	0.215	(5.5)	<b>Pair-4</b>	White/Brown	Brown
<b>Nominal cable weight—lb./kft. (kg/km)</b>	23	(34.5)	<b>Temperature Rating</b>		
<b>Max. installation tension—lb. (N)</b>	25	(110)	<b>Installation</b>	0°C to +50°C	
<b>Min. bend radius—in. (mm)</b>	1	(25.4)	<b>Operation</b>	-20°C to +75°C	

### Technical Data - Parametric Measurements

<b>Mutual Capacitance</b>	5.6 nF/100 m nom.
<b>DC resistance</b>	9.09 Ohms/100 m max.
<b>Skew</b>	45 ns/100 m max.
<b>Pair to ground Unbalance</b>	330 pF/100 m max.
<b>Velocity of Propagation</b>	70% nom.
<b>Input Impedance</b>	100 ± 13% 0.772-100 MHz 100 ± [13+15log (F/100)] 100-350 MHz
<b>DC Resistance Unbalance of a Pair</b>	5% max.

### Technical Data - Electrical

FREQ MHz	SRL (dB)	RL (dB)	IL (dB/100m)	PS-NEXT (dB)	NEXT (dB)	ACR (dB@100m)	PS-ACR (dB@100m)	ELFEXT (dB)	PS-ELFEXT (dB)
	min.	min.	max.	min.	min.	min.	min.	min.	min.
1	25.5	20.0	2.4	68.3	70.3	67.9	65.9	66.8	63.8
4	25.5	23.3	4.8	59.3	61.3	56.5	54.5	54.7	41.7

**LANmark-350 Patch**  
LANmark-350 Patch

10	25.5	25.5	7.7	53.3	55.3	47.7	45.7	46.8	43.8
20	25.5	25.0	11.0	48.8	50.8	39.8	37.8	40.7	37.7
31.25	24.4	24.4	13.9	45.9	47.9	34	32.0	36.9	33.9
62.5	22.7	22.7	20.2	41.4	43.4	23.2	21.2	30.8	27.8
100	21.5	21.1	26.1	38.3	40.3	14.2	12.2	26.8	23.8
200	19.8	19.8	38.5	33.8	35.8	—	—	20.7	17.7
300	18.8	18.8	48.6	31.2	33.2	—	—	17.2	15.8
350	18.4	18.4	53.3	30.2	32.2	—	—	15.9	12.9
400	18.1	18.1	57.6	29.3	31.3	—	—	14.7	11.7
450	17.8	17.8	61.8	28.5	30.5	—	—	13.7	10.7

IMPORTANT: Berk-Tek performance guarantees are based on swept-frequency testing and apply to all frequencies for the entire specified frequency range and are not limited to the table of data shown which are presented to demonstrate our guarantees at "representative" frequencies. Values above 350 MHz are for engineering information. Limited combustible version also available. Other jacket colors available.

**Supported Category 5e Applications**

STANDARD	APPLICATION	SPEED
IEEE 802.3	1000BASE-T	1 Gb/s
ATM	155Mb/s	155 Mb/s
IEEE 802.3	100BASE-TX	100 Mb/s
CDDI		100 Mb/s
IEEE 802.3	10BASE-T	10 Mb/s

**Selling information**

PLEASE NOTE: In the interest of product improvement, Berk-Tek, a Nexans company may make improvements or changes in the products, the programs or services described at any time without notice. Additionally, the information contained herein may include typographical errors or technical inaccuracies. Changes will be periodically made to address any such issues.