



CT504/350 Series	8.9Ω/100m	<b>Attenuation (dB/100m) (max)</b>	2.0	4.0	6.4	8.1	9.2	10.3	11.6	16.8	21.7	27.7	32.0	36.4	40.5	44.3
		<b>PSNEXT (dB/100m) (min)</b>	65.3	56.3	50.3	47.2	45.8	44.3	42.9	38.4	35.3	32.4	30.8	29.3	28.1	27.1
		<b>NEXT (dB/100m) (min)</b>	66.3	57.3	51.3	48.2	46.8	45.3	43.9	39.4	36.3	33.4	31.8	30.3	29.1	28.1
		<b>PSELFEXT (dB/100m) (min)</b>	61.0	49.0	41.0	36.9	35.0	33.0	31.1	25.1	21.0	17.2	15.0	13.0	11.5	10.1
		<b>ELFEXT (dB/100m) (min)</b>	64.0	52.0	44.0	39.9	38.0	36.0	34.1	28.1	24.0	20.2	18.0	16.0	14.5	13.1
		<b>Return Loss (dB) (min)</b>	25.0	25.0	25.0	25.0	25.0	24.3	23.6	21.5	20.1	----	----	----	----	----

[Back](#)

Toll Free: 800-966-0069 FAX: 847-795-8770

©2010. General Cable Technologies Corporation, Highland Heights, KY 41076. All rights reserved.

