



[Home](#) | [Contact](#) | [P/N Index](#)

PRODUCTS	COMPANY	ORDER	NEWS	TECHNICAL
----------	---------	-------	------	-----------

PRODUCTS / PRO-AUDIO, VIDEO & DATA CABLE / NETWORK CABLE / Heavy-duty Tactical Cat5e Cable

Heavy-duty Tactical Cat5e Cable



Heavy-duty tactical Category 5e cable for portable or remote patching of Ethernet networks or digital audio/video formats that utilize CAT5e type interconnects. The CT504HDX features the same double jacket construction as the original CT504HD for exceptional durability, but with solid conductors for lower attenuation that allows for the full recommended TIA distances for Cat5e network cable. The inner jacket maintains the proper physical spacing between pairs to achieve the ISO/IEC or TIA Cat5e specifications, while the durable TPE outer jacket protects the cable from physical damage or abuse. The CT504HDX is intended for use with Neutrik EtherCon® connectors and is also available from Gepco as preterminated cable assemblies.

FEATURES & BENEFITS

- Durable TPE Outer Jacket
- Flexible
- Unique Inner Belt Maintains Electrical Characteristics in Portable Applications
- Meets or Exceeds ISO/IEC & TIA Standards for Cat5e Cable
- Stranded or Solid 24 Gage Conductors
- 100MHz Bandwidth
- Terminates with Neutrik EtherCon® Connectors

APPLICATIONS

- Ethernet Network Patching
- For Portable Use or Remote Environments

Mechanical Specifications

Part #	# of Pairs	Nominal OD	Conductors	Insulation	Pair Color Code	Inner Jacket (Type, OD)	Outer Jacket	UL Type	Weight
CT504HD	4	.260"	24 AWG (41x40) Stranded TC	PE	White/Blue & Blue, White/Orange & Orange, White/Green & Green, White/Brown & Brown	Clear TPE, .190"	Black TPE	AWM Style 21144	26 lbs/Mft
<i>Heavy-duty Tactical Cat5e Cable: Extra-flexible</i>									
CT504HDX	4	.245"	24 AWG Solid BC	PE	White/Blue & Blue, White/Orange & Orange, White/Green & Green, White/Brown & Brown	Clear TPE, .190"	Black TPE	AWM Style 21144	26 lbs/Mft
<i>Heavy-duty Tactical Cat5e Cable: Low-loss</i>									

Electrical Specifications

Part #	DCR Max	DCR Unbal. Max	Mutual Capac. Max	Char. Impedance	Prop. Delay (Skew) Max	Vel. of Prop. (Non-plenum, Plenum)	Standards								
CT504HD	28.6 Ω	5%	17 pF/ft	100 Ω	45 ns/100m	69%	ISO/IEC 11801 Cat 5e Patch Cable								
			Freq. (MHz)		0.722	1	4	8	10	16	20	25	31.25	62.5	100
			Insertion Loss (dB/100m)		2.7	3.0	6.2	8.7	9.8	12.3	14.0	15.6	17.6	25.5	33.0
			PSNEXT (dB)		64.0	62.3	53.3	48.8	47.3	44.3	42.8	41.3	39.9	35.4	32.3
			PSACR (dB/100m)		61.3	59.3	47.2	40.1	37.6	32.0	28.9	25.7	22.4	9.9	-0.7
			PSELFEXT (dB/100m)		63.0	60.8	48.7	42.7	40.8	36.7	34.7	32.8	30.9	24.8	20.8
			RL (dB)		----	20.0	23.0	24.5	25.0	25.0	25.0	24.2	23.3	20.7	19.0

		17 pF/ft	100 Ω	45 ns/100m	69%	Meets or Exceeds TIA/EIA-568-B.2 Cat5e, ISO/IEC 11801								
CT504HDX	28.6 Ω	5%	Freq. (MHz)	0.722	1	4	8	10	16	20	25	31.25	62.5	100
			Insertion Loss (dB/100m)	1.8	2.0	4.1	5.8	6.5	8.2	9.3	10.4	11.7	17.0	22.0
			PSNEXT (dB)	70.0	68.3	59.3	54.8	53.3	50.3	48.8	47.3	45.9	41.4	38.3
			PSACR (dB/100m)	68.2	66.3	55.2	49.0	46.8	42.1	39.5	36.9	34.2	24.4	16.3
			PSELFEXT (dB/100m)	63.0	60.8	48.7	42.7	40.8	36.7	34.7	32.8	30.9	24.8	20.8
			RL (dB)	----	20.0	23.0	24.5	25.0	25.0	25.0	24.3	23.6	21.5	20.1

[Back](#)

Toll Free: 800-966-0069 FAX: 847-795-8770

©2010. General Cable Technologies Corporation, Highland Heights, KY 41076. All rights reserved.

