

1592A Multi-Conductor - Category 5e Nonbonded-Pair Patch Cable



For more Information
please call

1-800-Belden1



General Description:

CAT5e (200MHz), 4-Pair, U/UTP-Unshielded, CM Rated, Premise Patch Cable, 24 AWG Stranded (7x32) Bare Copper Conductors, Polyolefin Insulation, PVC Jacket, RJ-45 Compatible

Usage (Overall)

Suitable Applications: Premise Patch Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422

Physical Characteristics (Overall)

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 4 | 24 | 7x32 | BC - Bare Copper |

Total Number of Conductors: 8

Insulation

Insulation Material:

| Insulation Material |
|---------------------|
| PO - Polyolefin |

Outer Shield

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|--------------------------|
| PVC - Polyvinyl Chloride |

Outer Jacket Diameter:

| Nom. Dia. (mm) |
|----------------|
| 5.410 |

Pair

Pair Color Code Chart:

| Number | Color |
|--------|------------------------------|
| 1 | White/Blue Stripe & Blue |
| 2 | White/Orange Stripe & Orange |
| 3 | White/Green Stripe & Green |
| 4 | White/Brown Stripe & Brown |

Mechanical Characteristics (Overall)

| | |
|--|----------------|
| Operating Temperature Range: | -20°C To +75°C |
| Bulk Cable Weight: | 31.252 Kg/Km |
| Max. Recommended Pulling Tension: | 111.205 N |
| Min. Bend Radius/Minor Axis: | 25.400 mm |
| Min. Bend/Installation: | 53.340 mm |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---|-----|
| NEC/(UL) Specification: | CM |
| CEC/C(UL) Specification: | CM |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |

1592A Multi-Conductor - Category 5e Nonbonded-Pair Patch Cable

| | |
|---------------------------------------|---------------------------|
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| Telecommunications Standards: | Category 5e - TIA 568.C.2 |
| Other Specification: | ICEA 661 Category 5 Patch |

Flame Test

| | |
|-------------------|---------------------------------|
| UL Flame Test: | UL1685 Vertical Tray Flame Test |
| C(UL) Flame Test: | FT1 |
| CSA Flame Test: | FT1 |

Suitability

| | |
|------------------------|-----|
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | No |
| Suitability - Aerial: | No |
| Suitability - Burial: | No |
| Sunlight Resistance: | No |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

Capacitance (pF/m)

49.215

Maximum Capacitance Unbalance (pF/100 m): 330

Nominal Velocity of Propagation:

VP (%)

69

Maximum Delay:

Delay (ns/100 m)

510 @ 100MHz

Typical Delay Skew:

Delay Skew (ns/m)

0.121

Max. Delay Skew:

Delay Skew (ns/100 m)

45

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)

9.38

Max. Operating Voltage - UL:

Voltage

300 V RMS

Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)

3

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

| Freq. (MHz) | Max. Attenuation (dB/100 m) | Min. NEXT (dB) | Min. PSNEXT (dB) | Min. ACR (dB) | Min. PSACR (dB) | Min RL (dB) | Min. SRL (dB) |
|-------------|-----------------------------|----------------|------------------|---------------|-----------------|-------------|---------------|
| 1 | 2.5 | 65.3 | 62.3 | 62.8 | 59.8 | 20.0 | 23.0 |
| 4 | 4.9 | 56.3 | 53.3 | 51.4 | 48.4 | 23.0 | 23.0 |
| 8 | 6.9 | 51.8 | 48.8 | 44.9 | 41.9 | 24.5 | 24.5 |
| 10 | 7.8 | 50.3 | 47.3 | 42.5 | 39.5 | 25.0 | 25.0 |
| 16 | 9.9 | 47.3 | 44.3 | 37.4 | 34.4 | 25.0 | 25.0 |
| 20 | 11.1 | 45.8 | 42.8 | 34.7 | 31.7 | 25.0 | 25.0 |

METRIC MEASUREMENT VERSION

1592A Multi-Conductor - Category 5e Nonbonded-Pair Patch Cable

| | | | | | | | |
|-------|------|------|------|------|------|------|------|
| 25 | 12.5 | 44.3 | 41.3 | 21.8 | 28.8 | 24.3 | 24.3 |
| 31.25 | 14.1 | 42.9 | 39.9 | 28.8 | 25.8 | 23.6 | 23.6 |
| 62.5 | 20.4 | 38.4 | 35.4 | 18.0 | 15.0 | 21.5 | 21.5 |
| 100 | 26.4 | 35.3 | 32.3 | 8.9 | 5.9 | 20.1 | 20.1 |
| 155 | 33.7 | 32.5 | 29.5 | | | 15.8 | |
| 200 | 38.9 | 30.8 | 27.8 | | | 15.0 | |

Premise Cable Electrical Table 2:

| Freq. (MHz) | Input (Unfitted) Imp. (Ohms) | Fitted Impedance | Min. ELFEXT (dB) | Min. PSELFEXT (dB) |
|-------------|------------------------------|------------------|------------------|--------------------|
| 1 | 100 ± 15 | 100 ± 15 | 63.8 | 60.8 |
| 4 | 100 ± 15 | 100 ± 15 | 51.7 | 48.7 |
| 8 | 100 ± 15 | 100 ± 15 | 45.7 | 42.7 |
| 10 | 100 ± 15 | 100 ± 15 | 43.8 | 40.8 |
| 16 | 100 ± 15 | 100 ± 15 | 39.7 | 36.7 |
| 20 | 100 ± 15 | 100 ± 15 | 37.7 | 34.7 |
| 25 | 100 ± 15 | 100 ± 15 | 35.8 | 32.8 |
| 31.25 | 100 ± 15 | 100 ± 15 | 33.9 | 30.9 |
| 62.5 | 100 ± 15 | 100 ± 15 | 27.8 | 24.8 |
| 100 | 100 ± 15 | 100 ± 15 | 23.8 | 20.8 |
| 155 | 100 ± 25 | 100 ± 15 | 19.9 | 16.9 |
| 200 | 100 ± 25 | 100 ± 15 | 17.7 | 14.7 |

Notes (Overall)

Notes: Jacket sequentially marked at 2 ft. intervals. Third party verified to ANSI/TIA-568-C.2, Category 5e Patch.

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|----------------|----------|-------------|-------------|-------|---------------------------|
| 1592A F2VU1000 | 1,000 FT | 22,000 LB | GRAY, DEC | | CAT5E PATCH U/UTP CM BOX |
| 1592A F2V1000 | 1,000 FT | 24,000 LB | GRAY, DEC | | CAT5E PATCH U/UTP CM REEL |
| 1592A 002U1000 | 1,000 FT | 22,000 LB | RED | | CAT5E PATCH U/UTP CM BOX |
| 1592A 0021000 | 1,000 FT | 24,000 LB | RED | C | CAT5E PATCH U/UTP CM REEL |
| 1592A 003U1000 | 1,000 FT | 22,000 LB | ORANGE | | CAT5E PATCH U/UTP CM BOX |
| 1592A 0031000 | 1,000 FT | 24,000 LB | ORANGE | C | CAT5E PATCH U/UTP CM REEL |
| 1592A 004U1000 | 1,000 FT | 22,000 LB | YELLOW | | CAT5E PATCH U/UTP CM BOX |
| 1592A 0041000 | 1,000 FT | 24,000 LB | YELLOW | | CAT5E PATCH U/UTP CM REEL |
| 1592A 005U1000 | 1,000 FT | 22,000 LB | GREEN, DARK | | CAT5E PATCH U/UTP CM BOX |
| 1592A 0051000 | 1,000 FT | 24,000 LB | GREEN, DARK | C | CAT5E PATCH U/UTP CM REEL |
| 1592A 006U1000 | 1,000 FT | 22,000 LB | BLUE, LIGHT | | CAT5E PATCH U/UTP CM BOX |
| 1592A 0061000 | 1,000 FT | 24,000 LB | BLUE, LIGHT | C | CAT5E PATCH U/UTP CM REEL |
| 1592A 007U1000 | 1,000 FT | 22,000 LB | VIOLET | | CAT5E PATCH U/UTP CM BOX |
| 1592A 0071000 | 1,000 FT | 24,000 LB | VIOLET | C | CAT5E PATCH U/UTP CM REEL |
| 1592A 009U1000 | 1,000 FT | 22,000 LB | WHITE | | CAT5E PATCH U/UTP CM BOX |
| 1592A 0091000 | 1,000 FT | 23,000 LB | WHITE | C | CAT5E PATCH U/UTP CM REEL |
| 1592A 010U1000 | 1,000 FT | 22,000 LB | BLACK | | CAT5E PATCH U/UTP CM BOX |
| 1592A 0101000 | 1,000 FT | 24,000 LB | BLACK | C | CAT5E PATCH U/UTP CM REEL |

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 4 Revision Date: 08-14-2013

© 2015 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.