

# CAT5 ENHANCED 350MHz UTP (STRANDED)



## DESCRIPTION

Category-5E, 24AWG, UTP, 8C Stranded Bare Copper, PVC Jacket 1000ft.

## FEATURES

- High-Performance Data Cable
- 350MHz Bandwidth for Data Applications, Fast Ethernet and 155Mbps TP-PMD/CDDI
- Category-5E Unshielded Twisted Pair
- Easily Identified Color-Striped Pairs
- 24AWG Stranded Copper Conductors
- Exceeds TIA/EIA-568B.2
- ETL Listed
- 1000ft Pull Box



Dimensions 14.5H x 14.5L x 8.5W (inches)  
45pcs per pallet  
(Packaging may vary)

## SKU: 058 SERIES

### Technical Data

Rated Temperature (°C) 75  
Product Standard Certification CM

### Conductor

Size 24 AWG  
Diameter (±0.005mm) 7/0.2

### Insulation

Average Thickness (mm) 0.20  
Min. Point Thickness (mm) 0.18  
Insulation Diameter (±0.005mm) 0.98  
Twisted Pair Diameter (±0.01) 1.96

### Assembly Diameter

**Stranded Bare Copper**

24 AWG

7/0.2

**PE**

0.20

0.18

0.98

1.96

**4.20**

### Jacket

Average Thickness (mm) 0.60  
Min. Point Thickness (mm) 0.50  
Outer Diameter (±0.10mm) 5.40  
Rip Cord No

**PVC**

0.60

0.50

5.40

No

### Color of Pairs

Pair 1 Blue, White-Blue  
Pair 2 Orange, White-Orange  
Pair 3 Green, White-Green  
Pair 4 Brown, White-Brown

### Mechanical Characteristics

Test Object	Jacket
Test Material	PVC
Before Tensile Strength (Mpa)	>=13.8
Aging Elongation (%)	>=100
Aging Condition (°Cxhrs)	100x168
After Tensile Strength (Mpa)	>=85% of unaged
Aging Elongation (%)	>=50% of unaged
Cold Bend (-20±2° Cx4hrs)	No Crack

### Marking on Jacket

VERTICAL 4001453 cETLus VERIFIED CM UTP 4PR 24AWG CAT5E  
350MHz TIA/EIA-568B.2 STRANDED RoHS XXXFT

Jacket color available in  
Blue, Black, White, Green, Gray, Red, Yellow, Orange

## VERTICAL CABLE

954 454-3554 Florida Office

951 696-7772 California Office



[www.verticalcable.com](http://www.verticalcable.com)

Rev. 01/2011

Subject to change without notice.

# CAT5 ENHANCED 350MHz UTP (STRANDED)

## PERFORMANCE

### Electrical Characteristics:

1.0-350.0MHz Impedance (Ohms)	100±15
1.0-350.0MHz Delay Skew (ns/100m)	≤45
Pair-to-Ground Capacitance Unbalance (pF/100m)	≤330
Max. Conductor DC Resistance 20°C (ohms/km)	93.8
Resistance Unbalance (%)	≤5

Frequency (Mhz)	Return Loss (Min dB)	Attenuation Max	Next (Min dB)
0.772	19.4	1.8	67.0
1	20.0	2.0	65.3
4	23.0	4.1	56.3
8	24.5	5.8	51.8
10	25.0	6.5	50.3
16	25.0	8.2	47.3
20	25.0	9.3	45.8
25	24.3	10.4	44.3
31.25	23.6	11.7	42.9
62.5	21.5	17.0	38.4
100	20.1	22.0	35.3
250	17.8	34.5	29.3
350	16.6	40.2	27.2

Frequency (Mhz)	PSNext Min (dB)	ELFEXT Min(db/100m)	PSELFEXT Min(db/100m)	Delay Max (ns/100m)
0.772	64.0	66.0	63.0	575.0
1	62.3	63.8	60.8	570.0
4	53.3	51.7	48.7	552.0
8	48.8	45.7	42.7	546.7
10	47.3	43.8	40.8	545.4
16	44.3	39.7	36.7	543.0
20	42.8	37.7	34.7	542.0
25	41.3	35.8	32.8	541.2
31.25	39.9	33.9	30.9	540.4
62.5	35.4	27.8	24.8	538.6
100	32.3	23.8	20.8	537.6
250	26.3	15.8	12.8	536.3
350	24.2	12.9	9.9	535.9

## VERTICAL CABLE

954 454-3554 Florida Office  
951 696-7772 California Office

[www.verticalcable.com](http://www.verticalcable.com)

Rev. 01/2011

Subject to change without notice.