


Technical Data Sheet- Category 5E F/UTP Network

WEST PENN WIRE

2833 West Chestnut Street
Washington, PA 15301
Toll Free: (800) 245-4964
Fax: (724) 222-6420
www.westpenn-wpw.com



PART NUMBER:	4245F	Replaces: M58145 and M58196
DESCRIPTION:	24 AWG.- 4 PAIR Solid bare copper conductors, Shielded with an overall jacket.	
NEC RATING:	CMR	
APPROVALS:	(UL) C(UL) Listed or c(ETL)us Listed	
APPLICATION:	Indoor - Category 5E Applications- Ethernet, IP Cameras, Digital Integration Meets TIA/EIA 568B.2 Category 5e Specifications	

Construction Parameters:

Conductor	24 AWG Bare Copper
Stranding	Solid
Number of Conductors	8 (4 Pair)
Insulation	Thermoplastic
Shield	100% Foil with overlap
Drain	Yes 24AWG Tinned Copper
Jacket Material	PVC
Overall Cable Diameter	0.232" Nom.
Approximate Cable Weight	30 Lbs/1M' Nom.
Flame Rating	UL Riser Test

Electrical & Environmental Properties:

Operating Temperature Rating	-20°C To +60°C
Operating Voltage Rating	300 V RMS
DC Resistance per Conductor @ 20deg C	9.38 Ohms/100m Nom.
Mutual Capacitance	14pf/ft Nominal
Nominal Impedance	100 Ohms+/-15% (1-100Mhz)
Velocity of Propagation	72% Nominal
Delay Skew	30ns/100m MAX
Standards	TIA/EIA568-B.2
Insulation Colors	1.Blue/White-Blue, 2. Orange/White-Orange 3. Green/White-Green, 4. Brown/White-Brown
Jacket Color	Gray and Blue
RoHS Compliant	Yes

Electrical Specifications:

Frequency: MHz	1	10	25	100	200	350
Insertion Loss: dB/100m	2.0	6.5	10.4	22.0	28.8	16.3
NEXT: dB/100m	65.3	50.3	44.3	35.3	30.8	27.5
ACR: dB/100m	63.3	43.8	33.9	13.3	--	
PS-NEXT: dB/100m	62.3	47.3	41.3	32.3	27.8	24.2
PS-ACR: dB/100m	60.3	40.8	30.9	10.3	--	--
ELFEXT: dB/100m	63.8	43.8	35.8	23.8	17.8	
PS-ELFEXT: dB/100m	60.8	40.8	32.8	20.8	14.8	
RL: dB	20	25	24.3	20.1	18	16.3

Mechanical Properties:

Max. Recommended Pull Tension

25 lbs.

Min. Bend Radius (Install)

4x cable OD- 1inch Min.

Accessories:

Connectors: Jacks

KJS458TL-C5E – Cat5E F/UTP Jack

Connectors: Plugs

CN-EZSTP-EG Cat 5E RJ45 Shielded with External Ground
32-1900-xx Colored boots

Assemblies:

C5ES-314GY-xxFB
xx: 3.7.10.15.20.25

Tools:

TL-135 110 Punch down tool
TL-EZRJ45PROCT EZ Crimp Tool
TL-114 Crimp Tool for 32-2198UL

Patch Panel:

24458S-C5E Cat5E F/UTP 24 port Panel

Specification Issue Date: 10/13

This document is the property of West Penn Wire.
The information contained herein is considered
Proprietary and not to be reproduced by any means
Without written consent of West Penn Wire

Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our
knowledge, is true and accurate. However, since
conditions of use are beyond our control, all
recommendations or suggestions are presented
without guarantee or responsibility on our part. We
disclaim all liability in connection with the use of
information contained herein or otherwise.