

CONDUCTORS

- 24 AWG (SOLID) TINNED ANNEALED COPPER INSULATED WITH .010" NOMINAL WALL OF PVC TO A NOMINAL O.D. OF .040".
- EACH PAIR TWISTED WITH 1-1/4" NOMINAL LEFT HAND DIRECTION LAY
- 4 PAIR TOTAL COLOR CODED AS FOLLOWS:
 - BLACK & RED
 - BLACK & WHITE
 - BLACK & GREEN
 - BLACK & BLUE

NOTES

- OVERALL ALUMINUM/POLYESTER TAPE SHIELD, FOIL FACING OUTWARD
- 24 AWG SOLID TINNED COPPER DRAIN OVER TAPE SHIELD
- OVERALL .032" WALL GRAY PVC JACKET TO .220" NOMINAL FINAL DIAMETER
- PRINTED IN BLACK INK: "E90298 RU AWM STYLE 2464 80C 300V VW1"
- RoHS COMPLIANT

LISTINGS

- UL AWM STYLE 2464
- 80C 300 VOLTS

DATA GUIDE CABLE CORP.

ONE ERNRIC PLACE
 GARDNER, MA, 01440
 978-632-0900

REV	DESCRIPTION	DATE	APP.	TITLE		
				4PR 24 AWG O/A SHIELD AWM 2464		
				SCALE N/A	P/N 10A11-5	REV
0	FIRST ISSUE	1/13/10		DATE 1/10	DRN. BY WJD	APP. BY