

**Aerospace Part#:** 5410RKB

**LOW CAP CABLE**

**DESCRIPTION**

4 Pairs AWG 24/7x32 TC  
Individual Foil Shield CL2P CMP Foam FEP/E-CTFE Black

**PHYSICAL PROPERTIES**

**Pairs**

**Insulation**

# Pairs	AWG	Material	Material	Wall	Finished OD
4	24/7x32	Tinned Copper	Foam FEP	.015"	.054"

**Outer Shield Material**

**Drain Wire**

Shield Type	Material	Coverage	AWG	Material
Each Pair Shielded	Alum / Mylar	100%	24/7x32	Tinned Copper

**Outer Jacket Material**

**Cabling**

Jacket Material	Color	Wall	Overall O.D.	Lay
E-CTFE	Black	.012"	.294" Nom.	1"-2" Lay on Pair with Clear Mylar 3-4" Lay on Cable

**MECHANICAL PROPERTIES**

Operating Temp	Total Weight	Bend Radius
UL Rated -40C to 150C	38.7 lbs/m	15 X OD

**ELECTRICAL PROPERTIES**

Max. Operating Voltage	Capacitance (Cond. To Cond.)	Impedence
UL Rated 300V Power Ltd.	12.5 pf / ft nom.	100 ohms nom.

**INDUSTRY APPROVALS AND COMPLIANCE**

**Standards & Environmental Programs**

RoHS Compliant	YES
Suitability	Indoor, Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid
Applications	Communications, Audio, Instrumentation, Power-limited systems
Flame Test	NFPA 262 / FT6
NEC / (UL) Specification	CL2P / CMP
CEC / C (UL) Specification	CMP

**MISCELLANEOUS**

Markings: TYPE CL2P - TYPE CMP 24 AWG (UL), C(UL) 150C E130356 ROHS

Color: White-Blue/Blue-White White-Orange/Orange-White  
Code: White-Green/Green-White White-Brown/Brown-White

**Contact Us For More Information**

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

**LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA**

\* Specification subject to error and may change without notice