

# Lutze ETHERNET/ProfiNet Network Cable (C), Shielded PVC

## Flexible ETHERNET Network Cable with UL/CSA/CE Approvals



### Application

- Flexible Industrial Field Network cable for Fast Ethernet applications
- UL listed and compliant with NFPA 79 2007 requirements

### Characteristics

- Shielded for optimal data integrity in industrial environments
- Silicone/Talc free

### Technical Data

Impedance	100 Ω +/- 10% (1-100 MHz)
Loop Resistance	
AWG22	<110 Ω/km
AWG24	<165 Ω/km
AWG26	<273 Ω/km
Operating capacitance	< 50 pF/m
Nominal Voltage	250V
Test Voltage	1500V
Temperature	
Moving	-5°C - +75°C, CMG
Fixed	-30°C - +75°C, CMG
Bending radius fixed	6 x cable OD
Approvals	UL/CSA/CE CMG UL 1581 UL VW-1 CSA FT4 IEC 60332-1 Meets NEC 800 RoHS

### Construction

- Bare copper conductor per AWG
- Polyolefin insulation
- Shielded with foil tape and tinned copper braid
- Green PVC jacket

Part No.	Description No. of conductors	OD - Ø ca. mm	OD - Ø inches	Weight Lbs/Mft	Copper Lbs/Mft
----------	----------------------------------	------------------	------------------	-------------------	-------------------

### CAT 5e 100 Mhz, SF/UTP, CMG Industrial Ethernet, Ethernet IP

104335	(4x2xAWG 26/7 StC) WH/BU, BU; WH/OG, OG; WH/GN, GN; WH/BN, BN	6.3	0.248	36.2	20
--------	--	-----	-------	------	----

104336	(4x2xAWG 24/7 StC) WH/BU, BU; WH/OG, OG; WH/GN, GN; WH/BN, BN	7.6	0.299	44.9	37
--------	--	-----	-------	------	----

### CAT 6 250 MHz, S/FTP, CMG Industrial Ethernet, Ethernet IP, Gigabit Ethernet

104338	(4x(2xAWG26/7)St)C WH/BU, BU; WH/OG, OG; WH/GN, GN; WH/BN, BN	6.4	0.252	35.5	22
--------	--	-----	-------	------	----

### CAT 7 600 MHz, S/FTP, CMG Industrial Ethernet, Ethernet IP, 10 Gigabit Ethernet

104331	(4x(2xAWG26/7)St)C WH/BU, BU; WH/OG, OG; WH/GN, GN; WH/BN, BN	7.0	0.276	41.9	22
--------	--	-----	-------	------	----

### CAT 5 100 MHz, SF/UQP, UL600V AWM, CMG, PLTC Industrial Ethernet, ProfiNet, EtherCAT

104301	(2x2x0.22 Ø) (2 pair AWG 22/1) STAR QUAD Type A WH,YE; OG,BU	6.5	0.256	24.8	24.8
--------	---	-----	-------	------	------

104307	(2x2x0.22 Ø) (2 pair AWG 22/7) STAR QUAD Type B WH,YE; OG,BU	6.5	0.256	24.8	20.8
--------	---	-----	-------	------	------

Specifications are subject to change without prior notice