

38 Sutton Street Northbridge Ma 01534 508-234-6372

Product # 7391 **P/N#** C5514

Specification Sheet

Customer Part Number: 2408PSS-8HU Description: 4P 24 AWG TC SPVC O/A PVC

Construction:

Conductors: 24 7/32 TC Nom: 0.024

Insulation: 862-SRPVC Wall: 0.010 Nom: 0.044 + - 0.004

Color Code: Black-Red- White -Green-Blue

Note 1: There shall be Four (4) lengths of Black

Pairs : Lay 2.25 LHL Nom: 0.088 + - 0.015

PR#1 Black/Red PR#2 Black/Wht PR#3 Black/Grn PR# 4 Black/Blu

Note 2: Length of Lay maybe adjusted for roundness

 Cable:
 Lay
 2.00 LHL
 Nom:
 0.166+ - 0.015

 PR#1 Black/Red
 PR#2 Black/Wht
 PR#3 Black/Grn
 PR#4 Black/Blu with overall AMS (Foil Out)

Note 3: Filler(s) Maybe used type and color of may Vary

Note 4: Length of Lay maybe adjusted for roundness

Overall layout of product rotation of conductors and or pair(s) may vary to insure best possible

roundness and Look of product

Note 5: This product has No and Contains No Drain Wire.

Braid: 36 AWG TC Coverage 65% Nom: 0.190+ - 0.015

Jacket:

Compound 22871 PVC Wall: 0.032 Nom: 0.254 + - 0.015


Color: Gray

Note 6: Talc Powder or Paper/Tissue Tape Maybe be used for separator

Note 7: Print /Markings on Product may vary to better suit Industry approvals

Print

E174416 RU AWM 2464 80C 300V 24 AWG LL163715 CSA AWM IA 80C 300V OR TYPE CMG FT4 ROHS



Customer
Approval
igned Customer Approval Needed for ISO Documentation

Approvals RoHS UL 2464/CMG CSA C(UL) Rating 80*C / 300V

"This Cable Design is the intellectual property of Hueson Wire & Cable Co., Inc. intend for use by HuesonWire & Cable Co., Inc. and their customers. Treat this as a confidential controlled document"

Proprietary information

THIS DOCUMENT CAN ONLY BE DUPLICATED WITH THE WRITTEN PERMISSION FROM

HUESON WIRE AND CABLE