

Shielded Multi-Conductor FT-4



1-888-Electro
Fax 613-394-4101
SALES@ELECTROCABLES.COM

Stranded Tinned Copper Conductors*
SR-PVC Insulation, 100% Aluminum Foil Shield
Stranded Tinned Copper Drain, Grey PVC Jacket FT-4
-20° C to 105° C, Contact sales@electrocables.com for approval info

[Home](#)
[Electronic & Electrical Index](#)
[Search](#)
[Previous](#) [Next](#)
[Colour Code: ECI Chart 1](#)

ECI Catalogue Number	Conductor			Drain AWG Size	Wall Thickness		Nominal O.D. (inches)	Total Weight (lbs/km)	Colour Code
	No.	Size	Stranding		Insulation (inches)	Jacket (inches)			
5152403TFT4	3	24	7 x 32	24	.010	.020	.137	51	ECI Chart 1
5152404TFT4	4	24	7 x 32	24	.010	.020	.148	60	1
5152405TFT4	5	24	7 x 32	24	.010	.020	.155	68	1
5152406TFT4	6	24	7 x 32	24	.010	.023	.169	80	1
5152407TFT4	7	24	7 x 32	24	.010	.023	.187	90	1
5152408TFT4	8	24	7 x 32	24	.010	.023	.196	113	1
5152409TFT4	9	24	7 x 32	24	.010	.023	.205	127	1
5152410TFT4	10	24	7 x 32	24	.010	.023	.214	133	1
5152412TFT4	12	24	7 x 32	24	.010	.023	.229	153	2
5152415TFT4	15	24	7 x 32	24	.010	.023	.250	180	2
5152420TFT4	20	24	7 x 32	24	.010	.023	.280	220	2
5152425TFT4	25	24	7 x 32	24	.010	.030	.321	273	2
5152430TFT4	30	24	7 x 32	24	.010	.030	.345	313	2
5152440TFT4	40	24	7 x 32	24	.010	.030	.388	400	2
5152450TFT4	50	24	7 x 32	24	.010	.035	.480	476	2
5152251TFT4	2	22	7 x 30	24	.010	.020	.142	51	Black/Red
5152203TFT4	3	22	7 x 30	24	.010	.020	.150	63	1
5152204TFT4	4	22	7 x 30	24	.010	.020	.163	75	1
5152205TFT4	5	22	7 x 30	24	.010	.023	.182	100	1
5152206TFT4	6	22	7 x 30	24	.010	.023	.194	113	1
5152207TFT4	7	22	7 x 30	24	.010	.023	.205	127	1
5152208TFT4	8	22	7 x 30	24	.010	.023	.217	140	1

*Stranded **bare** copper conductors and special packaging and colours available upon request.
Aluminum or **Steel Interlock Armour** and Jacket available upon request.

The above data values are subject to change, please contact Electro Cables at sales@electrocables.com for verification of the above numbers to current manufacturing data values for your requirements or order.

This web site was last modified on Nov 27, 2015 , QMS registered to ISO 9001, Rev.60 All Rights Reserved.