



# JAMES MONROE

## WIRE & CABLE CORPORATION

P.O. Box 1203 So. Lancaster, MA 01561  
 Phone: 800-316-8877 or 978-368-0131  
 Fax: 978-368-1276  
<http://www.jamesmonroewire.com>

### ACKNOWLEDGEMENT

SALES ORDER NO.

**090231**

REV.  
0

REV DATE  
10/24/2016

CUSTOMER P.O. NUMBER <b>4500470493</b>	P.O. DATE <b>10/24/2016</b>	SALES REPRESENTATIVE <b>James Vaughan</b>	TAX EXEMPT
PAYMENT TERMS <b>1% 20, Net 30 Days</b>	F.O.B. <b>James Monroe</b>	FREIGHT PAYMENT <b>Collect</b>	CARRIER <b>Dule Pyle</b>
CUSTOMER ( 001320-000 )		SHIP TO ( 001320-010 )	
IEWC Corporation PO Box 510908 New Berlin, WI 53151-0908		IEWC Corporation Plant 3500 - Boston 11B Dana Hill Road Sterling, MA 01564	
ATTENTION: <b>Paul Cero</b>		BILL TO: <b>Same As Customer</b>	

ITEM	QUANTITY	PRODUCT NUMBER	DESCRIPTION	UNIT PRICE	EXTENSION(USD)
------	----------	----------------	-------------	------------	----------------

The following terms & conditions are in effect for all orders unless otherwise specified. Prices are subject to adjustment at time of shipment for changes in the Omega-Camden Copper Base. Length Tolerance: the seller reserves the right to ship and bill for length tolerance of +/- 10% of the specified quantity ordered. Freight is FOB COLLECT factory, So. Lancaster, MA. This order is valid for the bill of material listed. Revisions are subject to seller's acceptance. Delivery estimates are based on current production capacity.  
 Prices are subject to adjustment based on raw material cost at time of shipment.  
 All orders require written confirmation.

**Please sign for confirmation and return immediately!**

Accepted Specification on file .....  
 Proposed Specification attached ..... SPS  
 Length Tolerance ..... +10%/-10%  
 Estimated Week of Shipment..... See above  
 Must be returned within 24 hrs to maintain original shipping estimate  
 Accepted By [Signature] Date 11/1/2016



GENERAL PRODUCT SPECIFICATION  
 Phone 800-316-8877 Fax 978-368-1275  
 www.jamesmonroewire.com

Description: Nine Conductor, 24 AWG  
 Overall PVC Jacket

Date: 10/26/2016  
 JM Part Number: JM57764  
 Reference: 2409COFS-8JM

**Components** Nine 24 AWG Insulated Conductors

Conductor: 24 AWG, 7/32 tinned copper

Insulation: .016" nominal wall of PVC (see color code) .056"

**Cable Construction**

Cabling: Nine conductors cabled together with FR PP Fillers

Foil Shield: Aluminum-Mylar tape, Aluminum side OUT

Drain Wire: 24 AWG, 7/32 tinned copper

Jacket: .035" nominal wall of Gray PVC .276"

**Print (Black Inkjet)**

E66440 9/C 24 AWG 9\ AWM 2586 105C 600V VW-1 --- LL41103 CSA  
 AWM I/II A/B 105C 600V FT1

**Color Code**

- |           |           |
|-----------|-----------|
| 1. Black  | 6. Blue   |
| 2. White  | 7. Yellow |
| 3. Red    | 8. Brown  |
| 4. Green  | 9. Gray   |
| 5. Orange |           |

**Requirements**

Temperature: 105°C  
 Voltage: 600V

Approvals: UL AWM Style 2586  
 CSA AWM, FT1  
 CE-LVD and RoHS Compliant  
 (2011/65/EU)

Written By:	scs	10/26/2016	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				