



Description: Ten 24 AWG Conductors
 With An Overall Foil Shield
 and PVC Jacket

Date: 7/1/2013

JM Part Number: TBD

Reference: TBD

Components Ten 24 AWG Insulated Conductors

Conductor: 24 AWG, 7/32 tinned copper

Insulation: .009" nominal wall of SR-PVC (see below for color code) .042"

Cable Construction

Cabling: Ten Conductors

Drain Wire: 24 AWG, 7/32 tinned copper

Shield: Aluminum-Mylar tape, Aluminum side IN

Jacket: .025" nominal wall of Gray PVC .221"

Print

E138031 10/C 22 AWG SHIELDED 105C (UL) TYPE CM --- LL41103 CSA TYPE CMG 60C FT4

Color Code

- | | |
|----------|-----------|
| 1. Black | 6. Blue |
| 2. White | 7. Orange |
| 3. Red | 8. Yellow |
| 4. Green | 9. Violet |
| 5. Brown | 10. Gray |

Requirements

Temperature: 105C (UL)
 60C (CSA)

Approvals: UL Type CM
 CSA Type CMG, FT4

Voltage: 600V (Non-UL)

Written By:	rjc	7/1/2013	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				