

AEROSPACE WIRE & CABLE, INC.

CABLE SPECIFICATIONS

CUSTOMER :
PART NUMBER : 2670rbK

SHIP DATE :
QUANTITY :

1) DESCRIPTION : 6 Pair Shielded CL2P CMP
AWG 24/7x32 FEP/FEP Black

2) CONDUCTOR : AWG 24/7x32 Tinned Copper O.D.= .024"

3) INSULATION : FEP .006" wall O.D.= .036"

4) COLOR CODE : White-Blue/Blue-White White-Orange/Orange-White
White-Green/Green-White White-Brown/brown-White
White-Gray/Gray-White Red-Blue/Blue-Red


5) TWIST LAY : 2" Lay on Pairs 6" Lay on Cable

6) SHIELD : Aluminum / Mylar Shield with AWG 24/7x32 TC Drain Wire

7) BRAID : none

8) JACKET : Black FEP .010" wall O.D.= .204" nom.

9) MARKING : E111036 TYPE CL2P-E130356 TYPE CMP 24 AWG (UL), C(UL)

10) CAPACITANCE: 16-18 pF/foot nom.  FEP/FEP

11) WEIGHT : 30 lbs / 1000 feet

12) TEMPERATURE: Mat'l. Rated -80C to 200C VOLTAGE: UL 300V Power Ltd.