

**CONDUCTORS**

- 24 AWG (SOLID) TINNED ANNEALED COPPER INSULATED WITH .010" NOMINAL WALL OF PVC TO A NOMINAL O.D. OF .040".
- EACH PAIR TWISTED WITH 1-1/4" NOMINAL LEFT HAND DIRECTION LAY
- 6 PAIR TOTAL COLOR CODED AS FOLLOWS:
- BLACK & RED
- BLACK & WHITE
- BLACK & GREEN
- BLACK & BLUE
- BLACK & YELLOW
- BLACK & BROWN

**NOTES**

- FIBRALLATED POLYPRO FILLER AS REQUIRED
- OVERALL ALUMINUM/POLYESTER TAPE SHIELD, FOIL FACING OUTWARD
- 24 AWG SOLID TINNED COPPER DRAIN OVER TAPE SHIELD
- OVERALL .032" WALL GRAY PVC JACKET TO .260" NOMINAL FINAL DIAMETER
- PRINTED IN BLACK INK: "E90298 RU AWM STYLE 2464 80C 300V VW1"
- RoHS COMPLIANT

**LISTINGS**

- UL AWM STYLE 2464
- 80C 300 VOLTS

**DATA GUIDE CABLE CORP.**

ONE ERNRIC PLACE  
 GARDNER, MA, 01440  
 978-632-0900

REV	DESCRIPTION	DATE	APP.
0	FIRST ISSUE	1/13/10	

<p><b>DATA GUIDE CABLE CORP.</b>                  ONE ERNRIC PLACE                  GARDNER, MA, 01440                  978-632-0900</p>			
<p>TITLE                  6PR 24 AWG O/A SHIELD AWM 2464</p>			
SCALE N/A	P/N 10A11-6	REV	
DATE 1/10	DRN. BY WJD	APP. BY	