



P.O. Box 276, Trenton, Ontario, K8V 5R5
Voice: 888 - ELECTRO, Fax: 613 394 - 4101
email: info@electrocables.com
www.electrocables.com

Electro Cables Inc. Specification Sheet

Date: 5-Aug-10 Rev. 1

ECI Product#: **5302458TFT4**

Product Description: **Shielded Lo-Cap 8 pr. 24/7 Tinned Copper Conductor
FPO Insulation
O/A Foil & 24/7 STC Drain
PVC Jacket FT-4 75°C**

Conductor	24 AWG TINNED COPPER
Conductor Stranding	7
Nom Cond. DC Resistance @ 25°C, ohms/1000 ft	25.5
Insulating Material Type	Cellular Polyolefin
Overall Drain Wire Size	24/7 AWG TINNED COPPER
Jacket Material Type	PVC FT-4
Finished Cable OD, inches	0.35
Total Cable Weight (kgs/km)	80
Voltage Rating	150
Nominal Mutual Capacitance, pF/ft	12.5
Nom. Cond to Shield Capacitance, pF/ft	25
Impedance (ohms)	100
CSA Approval	c CSA us CMG 300V & CSA AWM 150V
Eu RoHS Compliant	Yes

(All of the above values are approximated to within 10%)

*** Put-ups available in any length required.**