

DESCRIPTION: 20 CONDUCTOR CONSISTING OF 6 TRIAD AND 1 PAIR
 24 AWG PVC INSULATED CABLE,
 UNSHIELDED WITH PVC JACKET
 UL AWM RATED 2661 105C 300 VOLTS
 CSA AWM RATED FT4

CONDUCTOR: 24 AWG SOLID TINNED ANNEALED COPPER IN ACCORDANCE
 WITH ASTM B-33-74

DIELECTRIC: .010" NOMINAL WALL THICKNESS PVC TO DIAMETER OF .040"

COLOR CODE:(STRIPE COVERAGE IS 50% +/- 10% CO-EXTRUDED)

- T1: ORANGE, ORANGE/WHITE, ORANGE/BLACK
- T2: RED, RED/WHITE, RED/BLACK
- T3: GREEN, GREEN/WHITE, GREEN/BLACK
- T4: LT. BLUE, LT BLUE/WHITE, LT BLUE/BLACK
- T5: YELLOW, YELLOW/WHITE, YELLOW/BLACK,
- T6: TAN, TAN/WHITE, TAN/BLACK,
- P1: WHITE AND BLACK

TRIAD ASSEMBLY:

LAY LENGTH:: 2" NOMINAL LEFT HAND DIRECTION

PAIR ASSEMBLY

LAY LENGTH: 2" NOMINAL LEFT HAND DIRECTION

CABLE ASSEMBLY:

LAY LENGTH: 3-1/2" NOMINAL LEFT HAND DIRECTION

FILLER: FIBRALATED POLYPROPYLENE AS REQUIRED FOR ROUNDNESS

BINDER: .001" NOMINAL THICKNESS POLYESTER TAPE

JACKET:

MATERIAL: THERMOPLASTIC PVC

COLOR: DATA GUIDE STANDARD GRAY

WALL THICKNESS: .032" NOMINAL

FINISHED CABLE DIAMETER: .300" NOMINAL

CABLE IDENTIFICATION:

TYPE: SURFACE PRINT ON JACKET

INK COLOR: CONTRASTING

LEGEND: "E90298 RU AWM STYLE 2661 105C 300V VW1

-- LL91737 CSA AWM I/II A/B 105C 300V FT4"

DATA GUIDE

CABLE CORP.

ONE ERNRIC PLACE
 GARDNER, MA. 01440
 978-632-0900

REV	DESCRIPTION	DATE	APP.
1	GRAY JKT; ADD CSA FT4	1/26/10	
-	INITIAL RELEASE	1/20/10	

TITLE		24 AWG 6TR, 1PR PVC/PVC 105C 300V	
SCALE	P/N	REV	
	10A18-8		
DATE	DRN. BY	APP. BY	
1/10	WJD		