



PRODUCT SPECIFICATION

November 1, 2010

Patti Starich
Industrial Electric Wire & Cable
P O Box 510908
5001 South Towne Drive
New Berlin, WI 53151-0908

Part Number: L8024(1T)-20C

Conductor: Twenty-four gauge solid tinned copper

Insulation: 10 mils of 105° C PVC

of Conductors: 20

Color Code: Blue, blue/black, orange, orange/black, green, green/black, white, white/black, black, black/white, blue/white, blue/red, orange/red, red, green/white, red/green, white/red, red/white, black/red, red/black

Cabling: Conductors concentrically cabled on a common axis with an overall polyester binder.

Jacket: 30 mils of gray 80° C PVC

Nominal OD. : .271"

Temp. Rating: 80° C

Voltage: 300 Volt

RoHS Compliant: Yes

(UL) Style: 2464

Copper Weight: 25 lbs per 1000 ft

Cable Weight: 56 lbs per 1000 ft

Shipping Tolerance: +/- 10%

Phone (860) 589-9035

www.multicable.com

Fax (860) 589-7520

This specification is proprietary information Owned by Multi/Cable Corporation and is submitted under a confidential relationship and may not be used or disclosed except for uses expressly granted by Multi/Cable. The information above is provided in good faith. It is believed to be accurate and represents the best information currently available to us. We make no warranty of merchantability, fitness for a particular purpose or of any other type, express or implied, with respect to products described or data or information provided, and we assume no liability resulting from such products, data or information. The user is required to comply with all laws and regulations relating to the purchase, use, storage and disposal of the products, and must be familiar with and follow generally accepted safe handling procedure. All dimensions herein are nominal.