

Deca Cables Inc.

150 North Murray Street
PO Box 777
Trenton, ON
Canada
K8V 5W6

Telephone: (613) 392-3585

Fax: (613) 392-7908

ISO 9002 - 1994

PRODUCT DATA SHEET

PART NUMBER	76-460
DESCRIPTION	LOW CAPACITANCE CABLE 12 1/2 PAIRS
CONDUCTOR	24 AWG TINNED COPPER
STRANDING	7 X 0.008"
CONDUCTOR DIAMETER	0.024"
INSULATION	CELLULAR POLYOLEFIN 80C
INSUL. COND. DIAMETER	0.045"
RESISTANCE	25.70 OHMS/1000FT
CHARACTERISTIC IMPEDANCE	100 OHMS
CAPACITANCE	12.5 PF/FT
DIELECTRIC CONSTANT	1.5
TIME DELAY	1.32 NSEC/FT
INDUCTANCE	0.998 mH/LOOP MILE
SHIELD	ALUM/POLYESTER FOIL (100% COVERAGE)
OVERALL DRAIN WIRE	24 AWG TINNED COPPER
JACKET	PVC 80C
JACKET THICKNESS	0.030"
FINISHED DIAMETER	0.379"
CSA CERTIFIED	CMG
UL RECOGNIZED	AWM STYLE 2919
FLAME RATING	FT4

The material contained in this document is presented in good faith and believed to be reliable and accurate. However, because testing conditions may vary and material quality or information that may be provided in whole or part by others may be beyond our control, no warranty, expressed or implied, is given and Deca Cables Inc. can assume no liability for results obtained or damages incurred through the application of the data and tests presented.