

## 20A NEMA | Black & White®

### Industrial Grade Black & White® Locking Devices

20A-347V AC, 480V AC and 600V AC

#### 2-Pole, 3-Wire Grounding

| Rating  | 20A-347V AC  |                  | 20A-480V AC  |                  | 20A-600V AC  |                  |
|---|--------------|------------------|--------------|------------------|--------------|------------------|
| NEMA  | L24-20P      | L24-20R          | L8-20P       | L8-20R           | L9-20P       | L9-20R           |
| Description                                       | Cat. No.     | Cat. No.         | Cat. No.     | Cat. No.         | Cat. No.     | Cat. No.         |
| <b>Plugs and Connectors</b>                       | <b>Plug</b>  | <b>Connector</b> | <b>Plug</b>  | <b>Connector</b> | <b>Plug</b>  | <b>Connector</b> |
| Black & White® Nylon Body                         | 3721         | 3723             | 2341         | 2343             | 2351         | 2353             |
| <b>Inlets and Outlets</b>                         | <b>Inlet</b> | <b>Outlet</b>    | <b>Inlet</b> | <b>Outlet</b>    | <b>Inlet</b> | <b>Outlet</b>    |
| Flanged Device                                    | —            | 3756             | 2345         | 2346             | 2355         | 2356             |
| <b>Receptacles</b>                                |              |                  |              |                  |              |                  |
| V-O-Max® Single Flush Receptacle                  | —            | 3720             | —            | 2340             | —            | 2350             |
| V-O-Max® Single Flush Receptacle, Isolated Ground | —            | —                | —            | —                | —            | 2350-IG          |



2341



2411

20A-125/250V, 3Ø 250V and 3Ø 480V

#### 3-Pole, 3-Wire Non-Grounding

| Rating                           | 20A-125/250V |                  | 20A-3Ø 250V  |                  | 20A-3Ø 480V  |                  |
|----------------------------------|--------------|------------------|--------------|------------------|--------------|------------------|
| NEMA                             | L10-20P      | L10-20R          | L11-20P      | L11-20R          | L12-20P      | L12-20R          |
| Description                      | Cat. No.     | Cat. No.         | Cat. No.     | Cat. No.         | Cat. No.     | Cat. No.         |
| <b>Plugs and Connectors</b>      | <b>Plug</b>  | <b>Connector</b> | <b>Plug</b>  | <b>Connector</b> | <b>Plug</b>  | <b>Connector</b> |
| Black & White® Nylon Body        | 2361         | 2363             | 2371         | 2373             | 2381         | 2383             |
| <b>Inlets and Outlets</b>        | <b>Inlet</b> | <b>Outlet</b>    | <b>Inlet</b> | <b>Outlet</b>    | <b>Inlet</b> | <b>Outlet</b>    |
| Flanged Device                   | 2365         | 2366             | 2375         | 2376             | 2385         | 2386             |
| <b>Receptacles</b>               |              |                  |              |                  |              |                  |
| V-O-Max® Single Flush Receptacle | —            | 2360             | —            | 2370             | —            | 2380             |



2413

20A-125/250V, 3Ø 250V and 3Ø 480V

#### 3-Pole, 4-Wire Grounding

| Rating  | 20A-125/250V |                  | 20A-3Ø 250V  |                  | 20A-3Ø 480V  |                  |
|---|--------------|------------------|--------------|------------------|--------------|------------------|
| NEMA  | L14-20P      | L14-20R          | L15-20P      | L15-20R          | L16-20P      | L16-20R          |
| Description                                       | Cat. No.     | Cat. No.         | Cat. No.     | Cat. No.         | Cat. No.     | Cat. No.         |
| <b>Plugs and Connectors</b>                       | <b>Plug</b>  | <b>Connector</b> | <b>Plug</b>  | <b>Connector</b> | <b>Plug</b>  | <b>Connector</b> |
| Black & White® Nylon Body                         | 2411         | 2413             | 2421         | 2423             | 2431         | 2433             |
| <b>Inlets and Outlets</b>                         | <b>Inlet</b> | <b>Outlet</b>    | <b>Inlet</b> | <b>Outlet</b>    | <b>Inlet</b> | <b>Outlet</b>    |
| Flanged Device                                    | 2415         | 2416             | 2425         | 2426             | 2435         | 2436             |
| <b>Receptacles</b>                                |              |                  |              |                  |              |                  |
| V-O-Max® Single Flush Receptacle                  | —            | 2410             | —            | 2420             | —            | 2430             |
| V-O-Max® Single Flush Receptacle, Isolated Ground | —            | 2410-IG          | —            | 2420-IG          | —            | —                |



2433



2416