

DESCRIPTION: 25 PAIR 24 AWG PVC INSULATED CABLE,  
OVERALL FOIL SHIELDED WITH PVC JACKET  
UL AND CSA RATED

CONDUCTOR: 24 AWG 7 STRANDS TINNED ANNEALED COPPER IN ACCORDANCE  
WITH ASTM B-3 AND B-8

DIELECTRIC: .010" NOMINAL WALL THICKNESS S-R PVC TO DIAMETER OF .044"

COLOR CODE: BELDEN CHART #3(SOLIDS)

PAIR ASSEMBLY:

LAY LENGTH: 1-1/4" NOMINAL LEFT HAND DIRECTION

CABLE ASSEMBLY:

LAY LENGTH: 6-1/2" NOMINAL LEFT HAND DIRECTION

FOIL SHIELD: .0015" NOMINAL THICKNESS ALUMINUM/POLYESTER,  
FOIL FACING OUTWARD

DRAIN: 24 AWG 7 STRAND TINNED COPPER OVER FOIL SHIELD

JACKET:

MATERIAL: THERMOPLASTIC PVC

COLOR: CHROME GRAY

WALL THICKNESS: .045" NOMINAL

FINISHED CABLE DIAMETER: .520" NOMINAL

CABLE IDENTIFICATION:

TYPE: SURFACE PRINT ON JACKET

INK COLOR: BLACK

LEGEND: "E123820 24 AWG TYPE CMG (UL) 75C OR AWM 2464 ---  
LL91737 CSA TYPE CMG"

DATA GUIDE

CABLE CORP.

ONE ERNRIC PLACE  
GARDNER, MA. 01440  
978-632-0900

REV	DESCRIPTION	DATE	APP.
-	INITIAL RELEASE	10/20/09	

TITLE 24 AWG 25/PR GRAY PVC/PVC SHIELD CABLE		
SCALE	P/N 06A31-4	REV
DATE 10/09	DRN. BY WJD	APP. BY