

CONDUCTORS

- 24 AWG (SOLID) TINNED ANNEALED COPPER INSULATED WITH .010" NOMINAL WALL OF PVC TO A NOMINAL O.D. OF .040".
- EACH PAIR TWISTED WITH 1-1/4" NOMINAL LEFT HAND DIRECTION LAY
- 25 PAIR TOTAL COLOR CODED AS FOLLOWS:
- BLACK & RED
- BLACK & WHITE
- BLACK & GREEN
- BLACK & BLUE
- BLACK & YELLOW
- BLACK & BROWN
- BLACK & ORANGE
- RED & WHITE
- RED & GREEN
- RED & BLUE
- RED & YELLOW
- RED & BROWN
- RED & ORANGE
- GREEN & BLUE
- GREEN & WHITE
- GREEN & BROWN
- GREEN & ORANGE
- GREEN & YELLOW
- WHITE & BLUE
- WHITE & BROWN
- WHITE & ORANGE
- WHITE & YELLOW
- BLUE & BROWN
- BLUE & ORANGE
- BLUE & YELLOW

NOTES

- FIBRALLATED POLYPRO FILLER AS REQUIRED
- OVERALL ALUMINUM/POLYESTER TAPE SHIELD, FOIL FACING OUTWARD
- 24 AWG SOLID TINNED COPPER DRAIN OVER TAPE SHIELD
- OVERALL .032" WALL GRAY PVC JACKET TO .450" NOMINAL FINAL DIAMETER
- PRINTED IN BLACK INK: "E90298 RU AWM STYLE 2464 80C 300V VW1"

-RoHS COMPLIANT

LISTINGS

- UL AWM STYLE 2464
- 80C 300 VOLTS

DATA GUIDE CABLE CORP.

ONE ERNRIC PLACE
GARDNER, MA, 01440
978-632-0900

REV	DESCRIPTION	DATE	APP.
0	FIRST ISSUE	1/13/10	

TITLE		
25PR 24 AWG O/A SHIELD AWM 2464		
SCALE N/A	P/N 10A11-9	REV
DATE 1/10	DRN. BY WJD	APP. BY