

Article Number: 250-03602

Description: One-Piece Surface Raceway, 1.75", 6ft Long, PVC, White,

120 ft/carton

| Base Data | | |
|--------------------------------|-----------------------|---|
| | Local Order Number | TSR3W-6A |
| | | |
| | Туре | TSR3-6A |
| | Color | White (WH) |
| | Features and benefits | Tamper resistant, self-locking hidden positive latch permits quick re-entry as well as providing a secure installation of premise wire. Fittings incorporate a minimum 1" bend radius per ANSI/TIA-568-C and 569-A standards. Rubber-based, foam-tape adhesive with high ultimate bond strength conforms to any surface. Flexible hinge allows the raceway to endure numerous openings without creating discoloration or stress cracking |
| | Quantity Per | carton |
| | Product Description | HellermannTyton's low voltage raceway (TSR) is a one piece, non-metallic, adhesive backed, latching raceway designed to aesthetically organize and route communications wires, including high speed UTP cable and fiber optic cable, from the telecom room to the work area. |
| | Short Description | One-Piece Surface Raceway, 1.75", 6ft Long, PVC, White, 120 ft/carton |
| Product Dimensions | | |
| | Length L (Imperial) | 6.0ft |
| | Length L (Metric) | 1.83m |
| | Width W (Imperial) | 1.75" |
| | Width W (Metric) | 44.45mm |
| | Height H (Imperial) | 1.0" |
| | Height H (Metric) | 25.40mm |
| Material and Specifications | | |
| | Material | Polyvinylchloride (PVC) |
| | Material Shortcut | PVC |
| | ROHS Compliant | Yes |

generated on: 6/23/2017

250-03602



| Logistic and Packaging | | | _ |
|---------------------------|-----------------------------|------------|---|
| | Package Quantity (Imperial) | 120ft | |
| | Package Quantity (Metric) | 36.6m | |
| | Customs Number(Schedule B) | 3925900000 | |

generated on: 6/23/2017