

83303E Multi-Conductor - MIL-W-16878/4 (Type E)

For more Information please call

1-800-Belden1



General Description:

26 AWG stranded (7x34) silver-plated copper conductors, cabled and color-coded, extruded TFE Teflon® insulation, silver plated copper braid shield (85% coverage), TFE teflon tape-wrapped jacket.

Physical Characteristics (Overall)			
Conductor			
AWG: # Conductors AWG Stranding Conductor Material			
1 26 7x34 SPC - Silver Plated Copper			
Total Number of Conductors:	1		
Insulation			
Insulation Material:			
Insulation Trade Name Insulation Material Wall Thickness	s (mm)		
Teflon® TFE - Tetrafluoroethylene 0.254			
Insulation Resistance:	100,000 Megaohms/1000 ft. @ 500 V DC		
Outer Shield Outer Shield Material:			
Type Outer Shield Material Coverage (%)			
Braid SPC - Silver Plated Copper 85			
Outer Jacket			
Outer Jacket Material: Outer Jacket Trade Name Outer Jacket Material Nom. Wall T	Thiskness (mm)		
Teflon® TFE - Tetrafluoroethylene 0.254	Thickness (mm)		
Overall Cable Overall Cabling Color Code Chart:			
Color			
White			
Overall Nominal Diameter:	1.930 mm		
Mechanical Characteristics (Overall)			
Operating Temperature Range:	-65°C To +200°C		
Bulk Cable Weight:	8.929 Kg/Km		
Bulk Cable Weight:	8.929 Kg/Km		
Max. Recommended Pulling Tension:	8.929 Kg/Km 58.271 N		
-			
Max. Recommended Pulling Tension: Min. Bend Radius/Minor Axis:	58.271 N 25.400 mm		
Max. Recommended Pulling Tension:	58.271 N 25.400 mm		
Max. Recommended Pulling Tension: Min. Bend Radius/Minor Axis: Applicable Specifications and Agency Compliance (0	58.271 N 25.400 mm		
Max. Recommended Pulling Tension: Min. Bend Radius/Minor Axis: Applicable Specifications and Agency Compliance (Applicable Standards & Environmental Programs	58.271 N 25.400 mm Overall)		
Max. Recommended Pulling Tension: Min. Bend Radius/Minor Axis: Applicable Specifications and Agency Compliance (C Applicable Standards & Environmental Programs EU Directive 2011/65/EU (ROHS II):	58.271 N 25.400 mm Overall) Yes		
Max. Recommended Pulling Tension: Min. Bend Radius/Minor Axis: Applicable Specifications and Agency Compliance (Applicable Standards & Environmental Programs EU Directive 2011/65/EU (ROHS II): EU CE Mark:	58.271 N 25.400 mm Overall) Yes Yes		
Max. Recommended Pulling Tension: Min. Bend Radius/Minor Axis: Applicable Specifications and Agency Compliance (C Applicable Standards & Environmental Programs EU Directive 2011/65/EU (ROHS II): EU CE Mark: EU Directive 2000/53/EC (ELV):	58.271 N 25.400 mm Overall) Yes Yes Yes		
Max. Recommended Pulling Tension: Min. Bend Radius/Minor Axis: Applicable Specifications and Agency Compliance (C Applicable Standards & Environmental Programs EU Directive 2011/65/EU (ROHS II): EU CE Mark: EU Directive 2000/53/EC (ELV): EU Directive 2002/95/EC (RoHS):	58.271 N 25.400 mm Overall) Yes Yes Yes Yes		
Max. Recommended Pulling Tension: Min. Bend Radius/Minor Axis: Applicable Specifications and Agency Compliance (Applicable Standards & Environmental Programs EU Directive 2011/65/EU (ROHS II): EU CE Mark: EU Directive 2000/53/EC (ELV): EU Directive 2002/95/EC (ROHS): EU RoHS Compliance Date (mm/dd/yyyy):	58.271 N 25.400 mm Overall) Yes Yes Yes Yes 01/01/2005		
Max. Recommended Pulling Tension: Min. Bend Radius/Minor Axis: Applicable Specifications and Agency Compliance (C Applicable Standards & Environmental Programs EU Directive 2011/65/EU (ROHS II): EU CE Mark: EU Directive 2000/53/EC (ELV): EU Directive 2002/95/EC (ROHS): EU ROHS Compliance Date (mm/dd/yyyy): EU Directive 2002/96/EC (WEEE):	58.271 N 25.400 mm Overall) Yes Yes Yes Yes 01/01/2005 Yes		
Max. Recommended Pulling Tension: Min. Bend Radius/Minor Axis: Applicable Specifications and Agency Compliance (C Applicable Standards & Environmental Programs EU Directive 2011/65/EU (ROHS II): EU CE Mark: EU Directive 2000/53/EC (ELV): EU Directive 2002/95/EC (ROHS): EU Directive 2002/95/EC (ROHS): EU Directive 2002/96/EC (WEEE): EU Directive 2003/11/EC (BFR):	58.271 N 25.400 mm Overall) Yes Yes Yes Overall Yes Yes Yes Yes Yes Yes Ot/01/2005 Yes Yes Yes Yes Yes Yes Yes Yes		
Max. Recommended Pulling Tension: Min. Bend Radius/Minor Axis: Applicable Specifications and Agency Compliance (Complicable Standards & Environmental Programs EU Directive 2011/65/EU (ROHS II): EU CE Mark: EU Directive 2000/53/EC (ELV): EU Directive 2002/95/EC (ROHS): EU RoHS Compliance Date (mm/dd/yyyy): EU Directive 2002/96/EC (WEEE): EU Directive 2003/11/EC (BFR): CA Prop 65 (CJ for Wire & Cable):	58.271 N 25.400 mm Overall) Yes Yes Yes Yes 01/01/2005 Yes Yes		

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

83303E Multi-Conductor - MIL-W-16878/4 (Type E)

Plenum/Non-Plenum				
Plenum (Y/N):	No			
Electrical Characteristics (Overall)				
Nom. Capacitance Conductor to Shield:				
Capacitance (pF/m) 146.333				
Nom. Conductor DC Resistance:				
DCR @ 20°C (Ohm/km) 127.959				
Max. Operating Voltage - UL:				
Voltage 600 V RMS				
Max. Recommended Current:				
Current 3 Amps per conductor @ 25°C				

Notes (Overall)

Notes: Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
83303E 0091000	1,000 FT	7.000 LB	WHITE	E	1 #26 TFE BRD TFE TAPE
83303E 009500	500 FT	3.500 LB	WHITE	E	1 #26 TFE BRD TFE TAPE

Notes:

E = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'

Revision Date: 09-04-2012 Revision Number: 5

© 2015 Belden, Inc All Rights Reserved

All hough Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information and belief at the date of its publication. The information provided in this Product Disclosure, is denied on the product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product tiself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.