

MULTICONDUCTOR CABLE

MULTICONDUCTOR BRAIDED SHIELD

105°C-PVC/NYLON - 600V
MIL-W-16878
TYPE BN



Description:

Each Conductor Stranded Tinned Copper, .010" Polyvinylchloride Insulation, Color Coded, Clear Nylon (Polyamide) Jacket, Conductors Cabled, Braided Tinned Copper Shield 90% Coverage, Gray Polyvinylchloride Jacket Overall

Characteristics:

Temperature Rating: -55°C to +105°C
Voltage Rating: 600V

WEICO NO.	NO. OF COND.	CONDUCTOR		NOM. JACKET THICKNESS (INCHES)	NOM. O.D. (IN)
		AWG	STRAND		
MIL-W-16878 Type BN Conductors Nominal Ins. Thickness--.010"--Nominal Nylon Thickness .003"					
6126	1	26	7/34	.010	.087
6226	2	26	7/34	.014	.138
6326	3	26	7/34	.014	.142
6426	4	26	7/34	.016	.162
6124	1	24	19/36	.010	.092
6224	2	24	19/36	.016	.152
6324	3	24	19/36	.016	.161
6424	4	24	19/36	.017	.172
6122	1	22	19/34	.010	.100

WEICO NO.	NO. OF COND.	CONDUCTOR		NOM. JACKET THICKNESS (INCHES)	NOM. O.D. (IN)
		AWG	STRAND		
6222	2	22	19/34	.016	.168
6322	3	22	19/34	.017	.178
6422	4	22	19/34	.019	.194
6120	1	20	19/32	.010	.106
6220	2	20	19/32	.019	.186
6320	3	20	19/32	.019	.196
6420	4	20	19/32	.021	.218
6118	1	18	19/30	.012	.120
6218	2	18	19/30	.021	.210
6318	3	18	19/30	.022	.227
6418	4	18	19/30	.023	.250
6116	1	16	19/29	.016	.137
6216	2	16	19/29	.023	.236
6316	3	16	19/29	.023	.240
6416	4	16	19/29	.025	.274

COLORS:

1 - White, 2 - Black,

3 - Red, 4 - Green

Standard Put-Ups: 1000 ft., 500 ft., 1000ft