



GENERAL PRODUCT SPECIFICATION
Phone 800-316-8877 Fax 978-368-1275
www.jamesmonroewire.com

Description: Four 26 AWG Insulated Conductors
Foil Shield and PVC Jacket

Date: 12/5/2012

JM Part Number: JM56802
Reference: TBD

Components	Four 26 AWG Insulated Conductors
Conductor:	26 AWG, 7/34 Tinned Copper
Insulation:	.015" Nominal Wall PVC (see color code) .049"

Overall Cable Construction

Cabling: Four insulated 26 AWG conductors cabled together

Shield: Aluminum-Mylar-Aluminum Tape

Drain Wire: 26 AWG, 7/34 Tinned Copper

Jacket: .036" Nominal Wall of Black PVC .197"

Print

E67179 4/C 26 AWG SHIELDED 90C (UL) TYPE CL2X OR AWM 2464
80C 300V ... RoHS

Color Code

- 1. White
- 2. Yellow
- 3. Orange
- 4. Green

Requirements

Temperature: 90C (UL CL2X) Approvals: UL TYPE CL2X
90C (AWM 2464) UL AWM Style 2464
RoHS Compliant

Voltage: 300V.

1/7/13 EQ Carlson Assemblytronics LLC

Written By:	rlc	12/5/2012	Rev. 0	Initial Issue
Revised By:	acs	1/7/2013	Rev. 1	Added JM Number
Revised By:				
Revised By:				