



DECA CABLES INC.  
150 North Murray Street  
P.O. Box 777  
Trenton, Ontario K8V 5W6  
Canada

Telephone: (613) 392-3585

Fax: (613) 392-7908

ISO 9001 - 2000

### PRODUCT DATA SHEET

<b>PART NUMBER</b>	73-031
<b>DESCRIPTION</b>	AWM SR/PVC 4C 26/7T SHIELDED FT4
<b>CONDUCTOR</b>	26 AWG TINNED COPPER
<b>STRANDING</b>	7 X 0.0063"
<b>CONDUCTOR DIAMETER</b>	0.019"
<b>INSULATION</b>	SR-PVC
<b>INSULATION THICKNESS</b>	0.009"
<b>INSUL. COND. DIAMETER</b>	0.038"
<b>RESISTANCE</b>	42.5 OHMS/1000FT
<b>SHIELD</b>	ALUM/MYLAR TAPE
<b>DRAIN WIRE</b>	26 AWG 7 x 0.0063" TINNED COPPER
<b>RIPCORD</b>	POLYESTER RIPCORD UNDER JACKET
<b>JACKET</b>	PVC
<b>JACKET THICKNESS</b>	0.015"
<b>FINISHED DIAMETER</b>	0.130"
<b>CSA CERTIFIED</b>	CMG, AWM II
<b>UL RECOGNIZED</b>	CM
<b>FLAME RATING</b>	FT4
<b>TEMPERATURE RATING</b>	-20C TO +105C

The material contained in this document is presented in good faith and believed to be reliable and accurate. However, because testing conditions may vary and material quality or information that may be provided in whole or part by others may be beyond our control, no warranty, expressed or implied, is given and Deca Cables Inc. can assume no liability for results obtained or damages incurred through the application of the data and tests presented.

Rev. 1

2005.01.06