



Deca Cables Inc.
 150 North Murray Street
 P.O. Box 777
 Trenton, Ontario K8V 5W6
 Canada

Website: www.decacables.com
 Telephone: (613) 392-3585
 Facsimile: (613) 392-7908
 Email: sales@decacables.com

ISO 9001:2000

PRODUCT DATA SHEET

Part No: 73-873

CONSTRUCTION SPECIFICATIONS

Description	AWM 2 Pair 26 AWG Shielded
Conductor	26 AWG 7 Strand Tinned Copper - Concentric
Conductor Diameter	0.019"
Insulation Type	High Density Polyethylene
Insulation Thickness	0.009"
Cable Assembly	Conductors are paired and then cabled together with an overall shield and drain. (foil in, drain in)
Conductor Identification	Black & Red, Brown & Orange
Drain Wire	24 AWG 7 Strand Tinned Copper
Overall Shielding Tape	Aluminum/mylar
Ripcord	None
Jacket	Flame Retardant PVC
Jacket Thickness	0.025" (minimum average)
Overall Cable Diameter	0.184"
Jacket Print	DELCO WIRE AND CABLE -40C #393132 CSA AWM II A/B80C 600V FT1 LL67097 RU AWM STYLE 2095 300V 80C E111002 ROHS (work order)

ELECTRICALS

Voltage	300V; STYLE 2095 / 600V; AWM II
Conductor Resistance	42.97 Ohms/Mft @20C

CERTIFICATIONS AND PHYSICAL PROPERTIES

CSA Certified	*CSA C22.2 No. 210.2, Appliance Wiring Material Products
UL RECOGNIZED	*UL 758, Appliance Wiring Material
Flame Test Rating	CSA FT1
Temperature Rating	80C
ROHS	Compliant
Cable Weight	30.15 kg/km
Copper Content	6.37 kg/km
Max Pull Tension	5.56 kgs
Min Bending Radius	2.25 inches (installed)
Min Installation Temp	-20C

Rev. 000

27-Jul-09