

**Description:** Eight 26 AWG Conductors  
 Overall Foil Shield, Braid Shield,  
 and PVC Jacket

**Date:** 6/6/2013

**JM Part Number:** JM56935

**Reference:** TBD

**Components**

Eight 26 AWG Insulated Conductors

Conductor: 26 AWG, 7/34 tinned copper

Insulation: .010" nominal wall of Semi-Rigid PVC (see color code) .039"

**Overall Cable**

Cabling: Core: One conductor with FRPP filler  
 Layer 1: Seven conductors cabled around core

Foil Shield: Aluminum-Mylar tape, Aluminum side OUT

Drain Wire: 26 AWG, 7/34 tinned copper

Shield: 36 AWG tinned copper braid, 90% coverage

Jacket: .032" nominal wall of Gray PVC .216"

**Color Code**

- |           |           |
|-----------|-----------|
| 1. Black  | 5. Yellow |
| 2. Brown  | 6. Green  |
| 3. Red    | 7. Blue   |
| 4. Orange | 8. Violet |

**Print**

**E66440 8/C 26 AWG SHIELDED  AWM 2464 80C 300V - - - LL41103 CSA  
 AWM I/II A/B 80C 300V FT1**

**Requirements**

Temperature: 80C  
 Voltage: 300V

Approvals: UL AWM Style 2464  
 CSA AWM, FT1

Written By:	rjc	6/6/2013	Rev. 0	Initial Issue
Revised By:	scs	6/26/2013	Rev. 1	Added JM Number, Revised conductor AWG size, OD's & legend
Revised By:				
Revised By:				