



DECA CABLES INC.
150 North Murray Street
P.O. Box 777
Trenton, Ontario K8V 5W6
Canada

Telephone: (613) 392-3585

Fax: (613) 392-7908

ISO 9001 - 2000

PRODUCT DATA SHEET

PART NUMBER	73-939
DESCRIPTION	AWM POLY/PVC 4PR 26/7T SH CSA FT1
CONDUCTOR	26 AWG TINNED COPPER
STRANDING	7 X 0.0063"
CONDUCTOR DIAMETER	0.019
RESISTANCE	42.5 OHMS/1000FT.
INSULATION	HIGH DENSITY POLYETHYLENE
INSULATION THICKNESS	0.009"
INSUL. COND. DIAMETER	0.038"
IMPEDANCE	115 OHMS
ASSEMBLY	CONDUCTORS ARE PAIRED AND THEN TWISTED TOGETHER WITH AN OVERALL SHIELD AND DRAIN (FOIL IN, DRAIN IN)
SHIELD	ALUMINUM / MYLAR TAPE
DRAIN WIRE	24 AWG 7 X 0.008" TINNED COPPER
RIPCORD	POLYESTER RIPCORD UNDER JACKET
JACKET	PVC
JACKET THICKNESS	0.025"
FINISHED DIAMETER	0.215"
CSA CERTIFIED	AWM II
UL RECOGNIZED	AWM STYLE 2095
FLAME RATING	FT1
ROHS	COMPLIANT

The material contained in this document is presented in good faith and believed to be reliable and accurate. However, because testing conditions may vary and material quality or information that may be provided in whole or part by others may be beyond our control, no warranty, expressed or implied, is given and Deca Cables Inc. can assume no liability for results obtained or damages incurred through the application of the data and tests presented.