

DATA CABLES

very good
EMC



DC 300 DS Multiconductor double shielded PVC signal and control cable



SAB BRÖCKSKES · D-VIERSEN · 03242526 DC 300 DS 26 AWG/25c 03242625 AWM Style 2464 80°C 300V CSA AWM I/II A/B 80°C 300V FT1 FT2

DC 300 DS is a double shielded UL/CSA approved multiconductor signal and control cable for use in American designed computer, data transmission and office equipment, process control and instrumentation.

Construction:

Conductor:	tinned copper strands acc. to ASTM B 286
Insulation:	semi-rigid PVC
Color code:	color code US 2 see page N/23
Stranding:	in layers
Screen:	double screen, Alu-foil, tinned copper braiding with tinned drain wire (AWG 24/7)
Jacket material:	PVC, YM1 acc. to DIN VDE 0207 part 5
Jacket color:	gray

Technical data:

Voltage:	UL/CSA: 300 V	
Peak operating voltage:	max. 350 V	
Testing voltage:	800 V	
Min. bending radius		
<i>fixed installation:</i>	5 x O.D.	
<i>free movement:</i>	10 x O.D.	
Radiation resistance:	8 x 10 ⁷ cJ/kg	
Temperature range		
<i>static:</i>	-30/+70 °C	UL/CSA: up to +80 °C
<i>flexing:</i>	-5/+70 °C	up to +80 °C
Burning characteristics:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2, UL VW1, CSA FT1 FT2	
Oil resistance:	acc. to internal standard, see page N/25	
Absence of harmful substances:	acc. to RoHS-guideline 2002/95/EG as well as GefStoffV appendix IV-no. 24, see page N/25	

Outstanding features:

- very good EMC characteristic
- small outer diameter
- small bending radius

item no.	no. of conductors	nominal outer-ø inch	mm	cable weight ≈ lbs/mft
▶ AWG 28/7				
03242802	2	0.169	4.3	14
03242803	3	0.173	4.4	16
03242804	4	0.181	4.6	17
03242805	5	0.193	4.9	20
03242807	7	0.201	5.1	23
03242809	10	0.236	6.0	29
03242812	12	0.244	6.2	32
03242814	14	0.252	6.4	34
03242818	18	0.272	6.9	41
03242825	25	0.311	7.9	50
▶ AWG 26/7				
03242602	2	0.177	4.5	16
03242603	3	0.181	4.6	17
03242604	4	0.193	4.9	20
03242605	5	0.201	5.1	24
03242607	7	0.213	5.4	26
03242609	10	0.252	6.4	34
03242612	12	0.260	6.6	38
03242614	14	0.268	6.8	41
03242618	18	0.291	7.4	50
03242625	25	0.335	8.5	63

item no.	no. of conductors	nominal outer-ø inch	mm	cable weight ≈ lbs/mft
▶ AWG 24/7				
03242402	2	0.185	4.7	18
03242403	3	0.193	4.9	20
03242404	4	0.201	5.1	24
03242405	5	0.217	5.5	28
03242407	7	0.228	5.8	32
03242409	10	0.272	6.9	42
03242412	12	0.280	7.1	47
03242414	14	0.287	7.3	52
03242418	18	0.315	8.0	64
03242425	25	0.366	9.3	82

item no.	no. of conductors	nominal outer-ø inch	mm	cable weight ≈ lbs/mft
▶ AWG 22/7				
03242202	2	0.197	5.0	21
03242203	3	0.205	5.2	25
03242204	4	0.217	5.5	28
03242205	5	0.232	5.9	34
03242207	7	0.248	6.3	40
03242209	10	0.295	7.5	54
03242212	12	0.303	7.7	60
03242214	14	0.315	8.0	67
03242218	18	0.346	8.8	83
03242225	25	0.406	10.3	110

Other dimensions and colors are possible on request.

F
5