## CABLE TECHNOLOGY PN: CT-E3227 16/PR #26 INDIVIDUALLY AND OVERALL SHIELDED

10/	1 K #20 INDIVIDUALET AND OVERALE SHIELDED			
CONDUCTORS:	#26 7/34 TINNED COPPER INSULATED WITH .010" POLYPROPYLENE			
SHIELDED PAIRS:	TWIST TWO (2) CONDUCTORS TOGETHER WRAP WITH A CLEAR POLYESTER TAPE PULL IN A #26 7/34 TINNED COPPER DRAIN WIRE WRAP WITH A FOIL FREE EDGED ALUMINUM/POLYESTER TAPE SHIELD (FOIL FACING IN) 25% OVERLAP, 100% COVERAGE			
<u>CABLING</u> :	CABLE SIXTEEN (16) INDIVIDUALLY SHIELDED PAIRS TOGETHER			
OVERALL TAPE SHIELD:	WRAP WITH AN ALUMINUM/POLYESTER TAPE SHIELD FOIL FACING OUT, 25% OVERLAP, 100% COVERAGE			
<u>DRAIN</u> :	PULL IN #26 7/34 TINNED COPPER DRAIN WIRE (OVER TAPE SHIELD)			
JACKET: NOM OD:	.035" CHROME PVC .450"			
NO JACKET PRINT				
COLOR CODE PAIRS:  1) GREEN / BLUE  2) GREEN / BROWN  3) WHITE / GREEN  4) BLACK / YELLOW  5) BLACK / RED  6) RED / BLUE  7) RED / ORANGE  8) RED / GREEN	9) RED / BROWN 10) RED / WHITE 11) BLACK / BLUE 12) BLACK / ORANGE 13) BLACK / GREEN 14) BLACK / BROWN 15) BLACK / WHITE 16) YELLOW / GREEN			
<u>RATINGS</u> :	-20°C TO +80°C 300V ROHS COMPLIANT			
<u>WEIGHT</u> :	APPROX 98 LBS PER 1000'			
I HAVE REVIEWED ABOVE SPECIFICATION AND IT CONFORMS TO ITEM ORDERED UNDER PO# NOTE AND EXCEPTIONS HERE →				
SIGNED: DATED:				

03/07/12 9:20 AM **PAGE: 1 OF 1** 

CTE3227