

Single Jacketed Buried Service Wire

Spec. 3502

BELL SYSTEM TYPE C SERVICE

Product Construction:**Conductors:**

- 22 AWG solid annealed copper

Insulation:

- High density polyethylene

Pairing:

- Varying pair lays

Core Filling:

- 80°C filling and flooding compounds

Core Wrap:

- Polyester tape

Shield:

- 0.004" corrugated commercial bronze or copper-clad steel tape

Rip Cord:

- Under the jacket

Jacket:

- Black, linear low density polyethylene

Application(s):

- Intended for use in buried service application to the subscriber loops

Compliances:

- Telcordia (Bellcore) Specification GR-3163-CORE
- RoHS Compliant (effective 1/1/10)

Packaging:

- Non-returnable plywood reels in lengths as shown above

**Nominal Cable Data**

CATALOG NUMBER	PAIRS AWG		O.D. (INCHES)	WEIGHT (LBS/MFT)	STANDARD LENGTH (FT)
2095160	3	22	0.30	55	1200
2095084	3	22	0.30	55	3000
2095086	3	22	0.30	55	5000
2095161	6	22	0.37	77	800
2095098	6	22	0.37	77	3000
2095099	6	22	0.37	77	5000

Data subject to change without notice. Contact your Customer Service Representative for latest information.