




303 / 316L Stainless Steel: Outer High Performance, High/Low Temp. & Corrosion Resistant

Part Numbers		Cable Range	Thread Type & Size	Dimensions in Inches (mm)			
-40°F to 212°F (-40°C to 100°C)	-31°F to 302°F (-35°C to 150°C)			A	B	TL	F <sub>1</sub> /F
		Inches (mm)	See page 56 for thread specs	Clearance Hole +.01" (+.25 mm)	Body Length	Thread Length	Wrench Flats
CD07AA-SS	CD07AA-SV	.12 - .26 (3 - 6.5)	PG 7	.49 (12.5)	.75 (19)	.20 (5)	.55 (14)
CD07AR-SS	CD07AR-SV	.08 - .20 (2 - 5)		PG 9	.60 (15.2)	.83 (21)	.24 (6)
CD09AA-SS	CD09AA-SV	.16 - .31 (4 - 8)	PG 11		.73 (18.5)	.87 (22)	.24 (6)
CD09AR-SS	CD09AR-SV	.08 - .24 (2 - 6)		PG 13 / 13.5	.80 (20.3)	.94 (24)	.26 (6.5)
CD11AA-SS	CD11AA-SV	.20 - .39 (5 - 10)	PG 16		.89 (22.5)	.91 (23)	.26 (6.5)
CD11AR-SS	CD11AR-SV	.12 - .28 (3 - 7)		PG 21	1.12 (28.4)	.94 (24)	.28 (7)
CD13AA-SS	CD13AA-SV	.24 - .47 (6 - 12)	PG 29		1.47 (37.3)	1.14 (29)	.31 (8)
CD13AR-SS	CD13AR-SV	.20 - .35 (5 - 9)		PG 36	1.85 (47)	1.38 (35)	.31 (8)
CD16AA-SS	CD16AA-SV	.39 - .55 (10 - 14)	PG 42		2.13 (54.1)	1.46 (37)	.35 (9)
CD16AR-SS	CD16AR-SV	.28 - .47 (7-12)		PG 48	2.34 (59.4)	1.50 (38)	.39 (10)
CD21AA-SS	CD21AA-SV	.51 - .71 (13 - 18)	M12 X 1.5		.47 (12)	.75 (19)	.26 (6.5)
CD21AR-SS	CD21AR-SV	.35 - .63 (9 - 16)		M16 X 1.5	.63 (16)	.87 (22)	.24 (6)
CD29AA-SS	CD29AA-SV	.71 - .98 (18 - 25)	M20 X 1.5		.79 (20)	.91 (23)	.24 (6)
CD29AR-SS	CD29AR-SV	.51 - .79 (13 - 20)		M25 X 1.5	.98 (25)	.94 (24)	.28 (7)
CD36AA-SS	CD36AA-SV	.87 - 1.26 (22 - 32)	M32 X 1.5		1.26 (32)	1.22 (31)	.31 (8)
CD36AR-SS	CD36AR-SV	.79 - 1.02 (20 - 26)		M40 X 1.5	1.57 (40)	1.46 (37)	.31 (8)
CD42AA-SS	CD42AA-SV	1.26 - 1.50 (32 - 38)	M50 X 1.5		1.97 (50)	1.46 (37)	.35 (9)
CD42AR-SS	CD42AR-SV	.98 - 1.22 (25 - 31)		M63 X 1.5	2.48 (63)	1.50 (38)	.39 (10)
CD48AA-SS	CD48AA-SV	1.46 - 1.73 (37 - 44)	M63 X 1.5		2.48 (63)	1.50 (38)	.39 (10)
CD48AR-SS	CD48AR-SV	1.14 - 1.38 (29 - 35)					

Stainless Steel Strain Relief Fittings can be used in many applications, where the environment dictates a corrosion proof solution.

### Typical Application:

- Off-shore
- Marine
- Chemical Plants
- Food Processing
- Clean Room
- Other Rugged Applications



Suggested Clearance Hole for Non-Threaded Mounting

**(303) INOX Stainless Steel** also available in **NPT Threads** upon request.



\*Note: CSA and CE Approvals only applies to Standard Fittings.

\*Note: VDE Approval only applies to Dome Fittings with Metric Threads.

Part Numbers		Cable Range	Thread Type & Size	Dimensions in Inches (mm)			
-40°F to 212°F (-40°C to 100°C)	-31°F to 302°F (-35°C to 150°C)			A	B	TL	F <sub>1</sub> /F
		Inches (mm)	See page 56 for thread specs	Clearance Hole +.01" (+.25 mm)	Body Length	Thread Length	Wrench Flats
CD09NA-6S	CD09NA-6V	.16 - .31 (4 - 8)	3/8" NPT	.68 (17.2)	.83 (21)	.59 (15)	.67 (17) / .75 (19)
CD09NR-6S	CD09NR-6V	.08 - .24 (2 - 6)		1/2" NPT	.83 (21.1)	.94 (24)	.51 (13)
CD13NA-6S	CD13NA-6V	.24 - .47 (6 - 12)	3/4" NPT		1.05 (26.7)	.98 (25)	.51 (13)
CD13NR-6S	CD13NR-6V	.20 - .35 (5 - 9)		1" NPT	1.35 (34.3)	1.14 (29)	.75 (19)
CD21NA-6S	CD21NA-6V	.51 - .71 (13 - 18)					
CD21NR-6S	CD21NR-6V	.35 - .63 (9 - 16)					
CD29NA-6S	CD29NA-6V	.71 - .98 (18 - 25)					
CD29NR-6S	CD29NR-6V	.51 - .79 (13 - 20)					

**The 316L material is much harder and ideal for direct exposure to salt water and chemical solutions in marine, off-shore, pharmaceutical, etc.**

Dome Fittings also available with the following approvals:



www.SealconEX.com

**(316L) INOX Stainless Steel** also available in **PG and Metric Threads** upon request.



Optional Locking Nuts, O-Rings & Other Accessories starting on Page 29 - 40.