


DATE	SYM	REVISION	RECORD	AUTH	DR	CK
7/98	A	98044R		FES	MJF	

SAME AS REV. -
DATED 04/23/82

JACKET:
POLYURETHANE, BLACK
OUTSIDE DIAMETER = 0.150/0.165 INCHES
MINIMUM WALL THICKNESS = 0.020 INCHES

SHIELD:
BRAIDED TINNED COPPER
MINIMUM COVERAGE = 90%

- INNER CONDUCTORS:**
1. RED IRRADIATED PVC, 28 AWG STRANDED
(7/36), TINNED COPPER
 2. WHITE IRRADIATED PVC, 28 AWG STRANDED
(7/36), TINNED COPPER
 3. BLACK IRRADIATED PVC, 28 AWG STRANDED
(7/36), TINNED COPPER
 4. UNINSULATED DRAIN WIRE, 28 AWG STRANDED
(7/36), TINNED COPPER
(DRAIN WIRE MUST CONTACT SHIELD)

 METROSONICS INC.		DRAWN BY MJF	
TOLERANCES		SCALE	APPR BY
DECIMAL +/-		/	
FRACTIONAL +/-	TITLE CABLE, SHIELDED		
ANGULAR +/-	DATE	DRAWING NUMBER	REV
	07/28/98	9002-1020	A

QUEST TECHNOLOGIES INC
CONTROLLED COPY # / *Q#*