

**Description:** Four Conductor Cable, 28 AWG  
 Overall Foil Shield and PVC Jacket

**Date:** 1/24/2008

**JM Part Number:** TBD

**Reference:** TBD

**Components** Four 28 AWG Insulated Conductors

Conductor: 28 AWG, 7/36 tinned copper

Insulation: .010" nominal wall of Semi-Rigid PVC (see color code) .035"

**Cable Construction**

Cabling: Four A Components

Drain Wire: 28 AWG, 7/36 tinned copper

Shield: Aluminum-Mylar tape, Aluminum side IN

Jacket: .033" nominal wall of Black PVC .155" ± .005"

**Print**

Printed at 24" maximum intervals as follows:

**E66440 9\ AWM STYLE 2517 4/C 28AWG 105C 300V --- LL41103 CSA AWM  
 I/II A/B 105C 300V FT1**

**Color Code**

1. Black                      2. White                      3. Red                      4. Green

**Requirements**

Temperature: 105°C

Voltage: 300V

Approvals: UL AWM Style 2517

CSA AWM, FT1

Cable Weight per 1000FT: 12.5 lbs

Written By:	rjc	1/24/2008	Rev. 0	Initial Issue
Revised By:	rjc	8/18/2010	Rev. 1	Changed OD to .155" ± .005", Revised print and added Cable Wt per MFT.
Revised By:				
Revised By:				