



Description: Eight 28 AWG Conductors With An Overall Foil Shield, and PVC Jacket

Date: 2/13/2009

JM Part Number: TBD
 Reference: TBD

Components Eight 28 AWG Insulated Conductors

Conductor: 28 AWG, 7/36 tinned copper

Insulation: .010" nominal wall of Semi-Rigid PVC (see color code) .035"

Cable Construction

Cabling: Core: One conductor and filler
 Layer 1: Seven conductors

Drain Wire: 28 AWG, 7/36 tinned copper

Foil Shield: Aluminum-Mylar tape, Aluminum side IN

Jacket: .035" nominal wall of Black PVC .190"

Print

E67179 8/C 28 AWG SHIELDED 75C (UL) TYPE CL2 OR AWM 2464
 80C 300V VW-1 -- LL41103 CSA TYPE CMG FT4

Color Code

- | | |
|-----------|-----------|
| 1. Black | 5. Orange |
| 2. Red | 6. Blue |
| 3. Violet | 7. Brown |
| 4. Green | 8. Yellow |

Requirements

Temperature: 80C (UL AWM Style 2464)
 75C (UL Type CM)

Approvals: UL Style 2464, VW-1
 UL Type CL2
 CSA Type CMG, FT4
 RoHS Compliant

Voltage: 300V

Written By:	rjc	2/13/2009	Rev. 0	Initial Issue
Revised By:	scs	3/3/2009	Rev. 1	Revised color code
Revised By:				
Revised By:				