

COONER WIRE

SPECIALTY WIRE & CABLE

9265 OWENSMOUTH AVE. CHATSWORTH, CA. 91311 www.coonerwire.com
PHONE: (818) 882-8311 FAX: (818) 709-8281

PAGE 1 OF 2

10 CONDUCTOR CABLE:

3 Conductor Sub-Cable (2)

Each Conductor:

- A. 28 AWG Stranding Bare Copper

Insulation:

- A. .005" TEFLON
- B. Color Coded: Black, Red, Green, Yellow, Brown, Violet
- C. O.D. over Insulation: .025" Nom.

28 AWG Shielded Twisted Pair (2)

Each Conductor:

- A. 28 AWG Stranding Bare Copper

Insulation:

- A. .005" FEP
- B. Color Coded: Whit/Blue and Orange/Gray
- C. O.D. over Insulation: .025" Nom.

Drain Wire:

- A. 28 AWG Stranding Bare Copper

Shield:

- A. .0015" Al/Mylar Tape (Foil Side In)
- B. 50% Lap

Cable:

- A. Two 3 Conductor Sub-Cables, Two 28 AWG Twisted Pairs And LS Polyester Fillers Around LS Polyester Core Filler.
.002" Unsintered PTFW Tape, 50% LAP.

Jacket:

- A. .030" Silicone Rubber
- B. Color: Black
- C. Overall Diameter: .201" Nom.

NO.	DATE	REASON FOR REVISION	BY		
				Drawn By: BB	Date: 5/9/08
				Approved: CW	Drawing No.
					CW8009

THIS IS AN ORIGINAL DOCUMENT AND MAY NOT BE COPIED, DISCLOSED OR USED IN WHOLE OR IN PART WITHOUT THE CONSENT OF COONER WIRE COMPANY.