



Description: Ten 28 AWG Conductors With An Overall Foil Shield, and PVC Jacket

Date: 2/10/2009

JM Part Number: TBD
Reference: TBD

Components Ten 28 AWG Insulated Conductors

Conductor: 28 AWG, 7/36 tinned copper

Insulation: .010" nominal wall of Semi-Rigid PVC (see color code) .035"

Cable Construction

Cabling: Core: Two conductors
Layer 1: Eight conductors

Drain Wire: 28 AWG, 7/36 tinned copper

Foil Shield: Aluminum-Mylar tape, Aluminum side IN

Jacket: .035" nominal wall of Black PVC .214"

Print

**E67179 10/C 28 AWG SHIELDED 75C (UL) TYPE CL2 OR AWM 2464
80C 300V VW-1 --- LL41103 CSA TYPE CMG FT4**

Color Code

- | | |
|-----------|-----------|
| 1. Black | 6. Blue |
| 2. Red | 7. Brown |
| 3. White | 8. Yellow |
| 4. Green | 9. Violet |
| 5. Orange | 10. Gray |

Requirements

Temperature: 80C (UL AWM Style 2464)
75C (UL Type CM)

Approvals: UL Style 2464, VW-1
UL Type CL2
CSA Type CMG, FT4
RoHS Compliant

Voltage: 300V

Written By:	rjc	2/10/2009	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				