

Description: Five 28 AWG Twisted Pairs
 Overall Foil Shield,
 and PVC Jacket

Date: 6/4/2015

JM Part Number: JM57482

Reference: 2810POFS-8JM

Components

Five 28 AWG Twisted Pairs

Conductor: 28 AWG, 7/36 tinned copper

Insulation: .010" nominal wall of SR-PVC (see below for color code) .035"

Pair Twist: Two 28 AWG singles twisted together

Overall Cable Construction

Cabling: Five 28 AWG twisted pairs cabled together with FR PP Fillers

Binder: Fleece tape

Drain Wire: 28 AWG, 7/36 tinned copper

Foil Shield: Aluminum-Mylar tape, Aluminum side IN

Ripcord: Nylon

Jacket: .032" nominal wall of Pressured Gray PVC .226"

Print (Black Inkjet)

**E138031 5PR 28 AWG 105C (UL) TYPE CM OR AWM 2464 80C 300V VW-1
 --- LL41103 CSA TYPE CMG 60C FT4 --- CE ROHS**

Color Code

1. White and Black
 2. White and Brown

3. White and Red
 4. White and Orange

5. White and Yellow

Requirements

Temperature: 105C
 Voltage: 300V

Approvals: UL Type CM
 UL AWM Style 2464
 CSA Type CMG, FT4
 CE-LVD and RoHS Compliant
 (2011/65/EU)

Written By:	scs	6/4/2015	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				